

Epson LQ-590IIN dot matrix printer 550 cps

Brand : Epson

Product code: C11CF39402A0

Product name : LQ-590IIN



- Fast print speed: USD speed of 550 characters per second at 10 characters per inch
- Increased reliability: Mean time between failure of 25,000 power-on hours
- Increased number of copies: Now original plus six copies
- Network capability: Supports both serial and Ethernet connections
- Same consumables: Uses the same ribbons as existing models

LQ-590IIN, Impact dot matrix, 24 pins, 24 needles, 550 chars/s, USB 2.0, 437x375x177 mm
 Epson LQ-590IIN. Maximum print speed: 550 cps, Character pitch: 10 cpi, Maximum number of copies: 6 copies. Paper tray media types: Envelopes, Labels, Roll, Continuous paper thickness range: 0.065 - 0.49 mm, Label thickness range: 0.16 - 0.19 mm. Product colour: Black, Buffer size: 128 KB, Sound pressure level (printing): 55 dB. Standard interfaces: Ethernet, Parallel, USB 2.0. Print head: 24-pin, Print head life: 400 million characters, Mean time between failures (MTBF): 25000 h

Printing		Weight & dimensions	
Maximum printing width (columns) *	80	Width	437 mm
Colour *	X	Depth	375 mm
Maximum print speed *	550 cps	Height	177 mm
Character pitch	10 cpi	Weight	7.2 kg
Maximum number of copies	6 copies	Packaging data	
Built-in barcodes	Code 128 (A/B/C), Code 39, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E	Quantity per pack	1 pc(s)
Character sets	PC437, PC708, PC720, PC850, PC858, PC864, PCAR864, ISO 8859-15, Roman 8, Italic	Package width	40 mm
Print speed	Ultra Speed-Draft: 10 cpi: 550 chars/s	Package depth	340 mm
		Package height	80 mm
		Package weight	9.28 kg
Paper handling		Other features	
Paper tray media types	Envelopes, Labels, Roll	Standard media sizes	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes, Cardboard
Continuous paper thickness range	0.065 - 0.49 mm	Connectivity technology	Wired
Label thickness range	0.16 - 0.19 mm	Print technology	Dot matrix
Multi-part paper thickness range	0.12 - 0.46 mm	Needles	24 Needles
Single sheet thickness range	0.065 - 0.14 mm	Compatible operating systems	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2008 R2, Windows Server 2016, Windows Vista, Windows XP
Features		Technical details	
Product colour *	Black	Sustainability certificates	ENERGY STAR
Buffer size *	128 KB	Logistics data	
Sound pressure level (printing) *	55 dB	Products per pallet	14 pc(s)
Country of origin	Indonesia	Pallet gross weight	0 g
Ports & interfaces		Pallet gross length	120 cm
Standard interfaces *	Ethernet, Parallel, USB 2.0	Pallet gross width	80 cm
Endurance		Pallet gross height	7.43 m
Print head *	24-pin	Products per pallet layer	2 pc(s)
Print head life	400 million characters	Products per pallet layer (UK)	4 pc(s)
Mean time between failures (MTBF)	25000 h	Products per pallet (UK)	28 pc(s)
Operational conditions		Pallet weight (UK)	0 g
Operating temperature (T-T)	5 - 35 °C	Pallet length (UK)	120 cm
Operating relative humidity (H-H)	10 - 80%	Pallet width (UK)	100 cm
System requirements		Pallet height (UK)	7.43 m
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows Vista, Windows XP	Harmonized System (HS) code	84433210
Server operating systems supported	Windows Server 2008 R2, Windows Server 2016		



8715946651361

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.