



## APC Smart-UPS UPS-virtalähde Linjainteraktiivinen 3 kVA 2700 W 10 AC-pistorasia(a)



**Tuotemerkki :** APC

**Tuotekoodi:** SMX3000HVNC

**Tuotteen nimi :** Smart-UPS

APC Smart-UPS. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 738 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 6,25 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 4U. Tuotteen leveys: 178 mm, Tuotteen syvyys: 483 mm, Tuotteen korkeus: 432 mm

Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount/Tower
Output power capacity *	3 kVA	Rack capacity	4U
Output power *	2700 W	Cable length	2.44 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	140 V	Display type	LCD
Input operation voltage (max) *	280 V	LED indicators	Status, Battery replacement
Input frequency *	50/60 Hz	Certification	C-tick, CE, CSA, EN 50091-1, EN 50091-2, EN 55022 Class A, EN 60950, FCC Part 15 Class A, GOST, IRAM, UL 1778, VDE, REACH
Output operation voltage (min)	208 V		
Output operation voltage (max)	240 V		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	645 J		
Hold time (min)	2 ms		
Hold time (max)	10 ms		
Efficiency	98.5%		
Emergency Power Off (EPO)	✓		
Noise level	55 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Auto-restart	✓		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler, C19 coupler	Operating temperature (T-T)	0 - 40 °C
Power plug	C20 coupler	Storage temperature (T-T)	-15 - 45 °C
AC outlets quantity	10 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
Number of output IEC jumpers	2	Storage relative humidity (H-H)	0 - 95%
SmartSlot	✓	Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
Battery		Technical details	
Battery technology	Sealed Lead Acid (VRLA)	Compliance certificates	RoHS
Battery capacity	738 VAh		
Typical backup time at full load	6.25 min		
Typical backup time at half load	18 min		
		Weight & dimensions	
		Width	178 mm
		Depth	483 mm
		Height	432 mm
		Weight	38.6 kg
		Package width	586 mm
		Package depth	633 mm
		Package height	330 mm
		Package weight	47.7 kg
		Packaging data	
		Rack mount kit	✓
		Cables included	RS-232

Battery		Packaging data	
Battery life (max)	5 year(s)	Temperature sensor	✓
Battery recharge time	3 h	Manual	✓
Hot-swap battery	✓	Software CD	✓
Automatic battery test	✓		
		Logistics data	
		Products per pallet	6 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Nominal output voltage	230 V
		Packaging content	Web/SNMP Management Card



0731304292623



731304292623



4054842444771

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.