APC

APC Smart-UPS UPS-virtalähde Linjainteraktiivinen 2,2 kVA 1980 W 9 AC-pistorasia(a)

Tuotemerkki : APC

Tuotteen nimi : Smart-UPS

Tuotekoodi: SMX2200RMHV2U

APC Smart-UPS. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 9 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 702 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 9,8 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 667 mm, Tuotteen korkeus: 85 mm

Features

UPS topology *	Line-Interactive
Output power capacity *	2.2 kVA
Output power *	1980 W
Waveform *	Sine
Input frequency *	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency regulation	50/60 Hz
Automatic Voltage Regulation (AVR)	✔
Surge energy rating	645 J
Response time	4 ms
Hold time (min)	2 ms
Hold time (max)	10 ms
Efficiency	98.1%
Emergency Power Off (EPO)	✔
Noise level	55 dB
Surge protection	✔
Audible alarm(s)	✔
Auto-restart	✔

Ports & interfaces

AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	9 AC outlet(s)
Number of output IEC jumpers	2
USB port	✔
SmartSlot	✔

Design

Form factor *	Rackmount/Tower
Rack capacity	2U
Cable length	1.83 m
Product colour *	Black
LED indicators	Battery replacement
Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, FCC Part 15 Class A, IEC 60950, IRAM, RCM, UL 1778, VDE, REACH, PEP, EOLI

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Technical details

Sustainability certificates	Green Premium
Compliance certificates	RoHS

Weight & dimensions

Width	432 mm
Depth	667 mm
Height	85 mm
Weight	37.3 kg
Package width	596 mm
Package depth	869 mm
Package height	243 mm
Package weight	45.4 kg

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	702 VAh
Typical backup time at full load	9.8 min
Typical backup time at half load	25.3 min
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	✔
Automatic battery test	✔

Packaging data

Rack mount kit	✔
Cables included	RS-232, USB cable
Manual	✔
Software CD	✔

Logistics data

Products per pallet	8 pc(s)
Harmonized System (HS) code	85078000

Other features

Nominal output voltage	230 V
Nominal input voltage	230 V

0731304272687

731304272687