

APC Smart-UPS X 2200VA UPS-virtalähde Linjainteraktiivinen 2,2 kVA 1980 W 10 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SMX2200HVNC

Tuotteen nimi: Smart-UPS X 2200VA


APC Smart-UPS X 2200VA. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Pistorasian tyypit: C13 liitin, C19 liitin, C20 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 702 ah, Akun latausaika: 3 h. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 178 mm, Tuotteen syvyys: 483 mm, Tuotteen korkeus: 432 mm





Features		Design	
UPS topology * Output power capacity * Output power * Waveform *	Line-Interactive 2.2 kVA 1980 W Sine	Form factor * Rack capacity Cable length Product colour *	Rackmount/Tower 2U 2 m Black
Input operation voltage (min) * 140 V Input operation voltage (max) * 280 V Input frequency * 50/60 Hz Output operation voltage (min) 208 V Output operation voltage (max) 240 V Output frequency 50/60 Hz Output frequency regulation +/- 3 Hz Output voltage regulation 5% Response time 10 ms Emergency Power Off (EPO) EMI/RFI noise filtering Noise level 55 dB	Display type LED indicators Certification	LED CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE	
	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m	
Surge protection Audible alarm(s) Web-based management	*	Technical details Compliance certificates Weight & dimensions	RoHS
Audible alarm modes Auto-restart Ports & interfaces	Battery replacement ✓	Width Depth Height	178 mm 483 mm 432 mm
AC outlet types Power plug AC outlets quantity USB 2.0 ports quantity Ethernet LAN (RJ-45) ports	C13 coupler, C19 coupler, C20 coupler C20 coupler 10 AC outlet(s) 1	Weight Package width Package depth Package height Package weight Packaging data	38.6 kg 586 mm 633 mm 330 mm 47.6 kg
Battery Battery technology Battery capacity	Sealed Lead Acid (VRLA) 702 Ah	Rack mount kit Cables included	✓ Input power cable, USB cable

Battery		Packaging data	
Battery recharge time	3 h	Quick installation guide	✓
Hot-swap battery Automatic battery test Cold start	* * *	Resource CD	✓
		Logistics data	
		Products per pallet Harmonized System (HS) code	6 pc(s) 85078000
		Other features	
		Output voltage	230 V





731304327158

0731304327158

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.