

## APC Smart-UPS 2200VA UPS-virtalähde Linjainteraktiivinen 2,2 kVA 1980 W 9 AC-pistorasia(a)

APC


Tuotemerkki : APC Tuotekoodi: SMT2200RMI2UNC

Tuotteen nimi: Smart-UPS 2200VA



APC Smart-UPS 2200VA. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Pistorasian tyypit: C20 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 9 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 509 ah, Akun latausaika: 5 h. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 480 mm, Tuotteen syvyys: 683 mm, Tuotteen korkeus: 86 mm

Features		Design	
Features  UPS topology * Output power capacity * Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency Surge energy rating Response time Emergency Power Off (EPO) Noise level	Line-Interactive 2.2 kVA 1980 W Sine 151 V 302 V 50/60 Hz 220 V 240 V 50/60 Hz 375 J 4 ms 0 55 dB	Form factor * Rack capacity Product colour * Display type LED indicators  Certification  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	Rackmount 2U Black LCD  ✓ CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE  0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m
Surge protection	1	Non-operating altitude	0 - 15000 m
Audible alarm(s)  Web-based management  Audible alarm modes  Auto-restart	Battery replacement	<b>Technical details</b> Sustainability certificates Compliance certificates	Green Premium RoHS
	•	Weight & dimensions	
Ports & interfaces  AC outlet types  Power plug  AC outlets quantity  USB 2.0 ports quantity  Ethernet LAN (RJ-45) ports  Battery	C20 coupler C20 coupler 9 AC outlet(s) 1	Width Depth Height Weight Package width Package depth Package height Package weight	480 mm 683 mm 86 mm 42.2 kg 600 mm 980 mm 254 mm 49.6 kg
Battery technology Battery capacity	Sealed Lead Acid (VRLA) 509 Ah	Packaging data	Š
Battery recharge time Hot-swap battery Automatic battery test Cold start	5 h	Rack mount kit Cables included Quick installation guide Resource CD	✓ Input power cable, USB cable ✓
		Logistics data Products per pallet Harmonized System (HS) code Other features	8 pc(s) 85078000
		Output voltage	230 V





731304327691

0731304327691

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.