

## APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 6 kVA 6000 W 10 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SRT6KXLI

Tuotteen nimi: Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 6 kVA, Lähtöteho: 6000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 902 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 2,5 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Näytön tyyppi: LCD. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE





Features		Design	
UPS topology * Output power capacity * Output power * Waveform * Input operation voltage (min) *	6000 W Sine	Form factor * Product colour * Display type LED indicators International Protection (IP) code	Rackmount/Tower Black LCD Status IP20
Input operation voltage (max) *	275 V	Operational conditions	
Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency regulation Surge energy rating Number of output phases Efficiency	40 - 70 Hz 220 V 240 V 50/60 Hz 480 J 1 94.4% 3:1	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Crest factor		Certificates	
Emergency Power Off (EPO) Output voltage Total Harmonic Distortion (THD) Noise level	✓ 3% 55 dB	Compliance certificates  Certification	RoHS REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
Surge protection	<b>√</b>	Packaging content	
Audible alarm(s) Auto-restart	✓ ✓	Cables included Quick installation guide	USB cable ✓
Ports & interfaces		Sustainability	
AC outlet types	C13 coupler, C19 coupler	Sustainability certificates	ENERGY STAR

Ports & interfaces		Weight & dimensions	
Power plug Hardwire  AC outlets quantity 10 AC outlet(s)  Number of output IEC jumpers 2  USB port ✓	10 AC outlet(s) 2	Width Depth Height Weight	174 mm 719 mm 432 mm 60 kg
Serial interface	✓	Packaging data	
Serial interface type	RJ-45	Temperature sensor	✓
SmartSlot	•	Warranty card	✓
Battery		Software CD	✓
Battery technology  Battery capacity  Typical backup time at half load  Typical backup time at half load  Sealed Lead Acid (VRLA)  902 VAh  2.5 min  8.7 min	902 VAh 2.5 min	Package width Package depth Package height Package weight	610 mm 960 mm 370 mm 67 kg
Battery life (max)	5 year(s)	Logistics data	
Battery recharge time 1.5 h  Hot-swap battery  Automatic battery test  Cold start  ✓	✓ ✓	Products per pallet Harmonized System (HS) code Total carbon footprint (kg of CO2e)	6 pc(s) 85078000 13539.46
	•	Other features	
		Packaging content	Removable support feet Web/SNMP Management Card





731304301660

0731304301660

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.