



## APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 6 kVA 6000 W 10 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SRT6KXLI

**Tuotteen nimi :** Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 6 kVA, Lähtöteho: 6000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Pääte, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 902 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 2,5 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 174 mm, Tuotteen syvyys: 719 mm, Tuotteen korkeus: 432 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	6 kVA	Cold start	✓
Output power *	6000 W		
Waveform *	Sine		
Input operation voltage (min) *	100 V		
Input operation voltage (max) *	275 V		
Input frequency *	40 - 70 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency regulation	50/60 Hz		
Surge energy rating	480 J		
Number of output phases	1		
Efficiency	94.4%		
Crest factor	3:1		
Emergency Power Off (EPO)	✓		
Output voltage Total Harmonic Distortion (THD)	3%		
Noise level	55 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler	Form factor *	Rackmount/Tower
		Product colour *	Black
		Display type	LCD
		LED indicators	Status
		International Protection (IP) code	IP20
		Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	ENERGY STAR
		Compliance certificates	RoHS

Ports & interfaces		Weight & dimensions	
Power plug	Terminal	Width	174 mm
AC outlets quantity	10 AC outlet(s)	Depth	719 mm
Number of output IEC jumpers	2	Height	432 mm
USB port	✓	Weight	60 kg
Serial interface	✓	Package width	610 mm
Serial interface type	RJ-45	Package depth	960 mm
SmartSlot	✓	Package height	370 mm
		Package weight	67 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Cables included	USB cable
Battery capacity	902 VAh	Temperature sensor	✓
Typical backup time at full load	2.5 min	Quick installation guide	✓
Typical backup time at half load	8.7 min	Warranty card	✓
Battery life (max)	5 year(s)	Software CD	✓
Battery recharge time	1.5 h		
Hot-swap battery	✓	Logistics data	
		Products per pallet	6 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Packaging content	Removable support feet Web/SNMP Management Card



0731304301660



731304301660

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.