



## APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 5 kVA 4500 W 12 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SRT5KXLI

**Tuotteen nimi :** Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 5 kVA, Lähtöteho: 4500 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 12 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 845 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Tuotteen väri: musta, Näytön tyyppi: LCD, LED-merkkivalot: Tila. Tuotteen leveys: 130 mm, Tuotteen syvyys: 719 mm, Tuotteen korkeus: 432 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	5 kVA	<b>Design</b>	
Output power *	4500 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	100 V	LED indicators	Status
Input operation voltage (max) *	275 V	International Protection (IP) code	IP20
Input frequency *	40 - 70 Hz	Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
Output operation voltage (min)	220 V	<b>Operational conditions</b>	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency regulation	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Surge energy rating	480 J	Operating relative humidity (H-H)	0 - 95%
Efficiency	94.1%	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
Noise level	55 dB	<b>Technical details</b>	
Surge protection	✓	Sustainability certificates	ENERGY STAR
Audible alarm(s)	✓	Compliance certificates	RoHS
Auto-restart	✓	<b>Weight &amp; dimensions</b>	
<b>Ports &amp; interfaces</b>		Width	130 mm
AC outlet types	C13 coupler, C19 coupler	Depth	719 mm
Power plug	Hardwire	Height	432 mm
AC outlets quantity	12 AC outlet(s)	Weight	54.4 kg
Number of output IEC jumpers	2	Package width	610 mm
USB port	✓		
Serial interface	✓		

Ports & interfaces		Weight & dimensions	
Serial interface type	RJ-45	Package depth	960 mm
SmartSlot	✓	Package height	330 mm
		Package weight	63.6 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Cables included	USB cable
Battery capacity	845 VAh	Temperature sensor	✓
Typical backup time at full load	4 min	Quick installation guide	✓
Typical backup time at half load	11.8 min	Warranty card	✓
Battery life (max)	5 year(s)	Software CD	✓
Battery recharge time	1.5 h		
Hot-swap battery	✓	Logistics data	
Automatic battery test	✓	Products per pallet	6 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Packaging content	Comms cable Removable support feet Web/SNMP Management Card



0731304301615



731304301615

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.