



APC Smart-UPS UPS-virtalähde Linjainteraktiivinen 1 kVA 640 W 4 AC-pistorasia(a)



Tuotemerkki : APC

Tuotekoodi: SUA1000RMI1U

Tuotteen nimi : Smart-UPS

APC Smart-UPS. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 640 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 4 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 216 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 5,4 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 1U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE, PEP, EOLI

Features		Design	
UPS topology *	Line-Interactive	LED indicators	Battery replacement
Output power capacity *	1 kVA	Operational conditions	
Output power *	640 W	Operating temperature (T-T)	0 - 40 °C
Waveform *	Sine	Storage temperature (T-T)	-15 - 45 °C
Input operation voltage (min) *	151 V	Operating relative humidity (H-H)	0 - 95%
Input operation voltage (max) *	302 V	Storage relative humidity (H-H)	0 - 95%
Input frequency *	50/60 Hz	Operating altitude	0 - 3000 m
Surge energy rating	480 J	Non-operating altitude	0 - 15000 m
Noise level	55 dB	Certificates	
Surge protection	✓	Compliance certificates	RoHS
Audible alarm(s)	✓	Certification	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE, PEP, EOLI
Ports & interfaces		Packaging content	
AC outlet types	C13 coupler	Rack mount kit	✓
Power plug	C14 coupler	Cables included	RS-232, USB cable
AC outlets quantity	4 AC outlet(s)	Manual	✓
Number of output IEC jumpers	2	Weight & dimensions	
USB port	✓	Width	432 mm
Serial interface	✓	Depth	660 mm
Serial interface type	RS-232	Height	44 mm
SmartSlot	✓	Weight	21.8 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Software CD	✓
Battery capacity	216 VAh	Package width	559 mm
Typical backup time at full load	5.4 min	Package depth	775 mm
Typical backup time at half load	14.5 min	Package height	191 mm
Battery life (max)	6 year(s)	Package weight	25.4 kg
Battery recharge time	2 h	Logistics data	
Hot-swap battery	✓	Products per pallet	8 pc(s)
Automatic battery test	✓	Harmonized System (HS) code	85078000
Design		Other features	
Form factor *	Rackmount	Interface	DB-9 RS-232, SmartSlot, USB
Rack capacity	1U	Input connection type	IEC-320 C14
Product colour *	Black	Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304123897



731304123897

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.