



APC Smart-UPS UPS-virtalähde Linjainteraktiivinen 1 kVA 640 W 4 AC-pistorasia(a)



Tuotemerkki : APC

Tuotekoodi: SUA1000RMI1U

Tuotteen nimi : Smart-UPS

APC Smart-UPS. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 640 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 4 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 216 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 5,4 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 1U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 660 mm, Tuotteen korkeus: 44 mm

Features		Design	
UPS topology *	Line-Interactive	Product colour *	Black
Output power capacity *	1 kVA	LED indicators	Battery replacement
Output power *	640 W	Certification	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE, PEP, EOL
Waveform *	Sine		
Input operation voltage (min) *	151 V		
Input operation voltage (max) *	302 V		
Input frequency *	50/60 Hz		
Surge energy rating	480 J		
Noise level	55 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler	Operating temperature (T-T)	0 - 40 °C
Power plug	C14 coupler	Storage temperature (T-T)	-15 - 45 °C
AC outlets quantity	4 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
Number of output IEC jumpers	2	Storage relative humidity (H-H)	0 - 95%
USB port	✓	Operating altitude	0 - 3000 m
Serial interface	✓	Non-operating altitude	0 - 15000 m
Serial interface type	RS-232		
SmartSlot	✓		
Battery		Technical details	
Battery technology	Sealed Lead Acid (VRLA)	Compliance certificates	RoHS
Battery capacity	216 VAh		
Typical backup time at full load	5.4 min		
Typical backup time at half load	14.5 min		
Battery life (max)	6 year(s)		
Battery recharge time	2 h		
Hot-swap battery	✓		
Automatic battery test	✓		
Design		Weight & dimensions	
Form factor *	Rackmount	Width	432 mm
Rack capacity	1U	Depth	660 mm
		Height	44 mm
		Weight	21.8 kg
		Package width	559 mm
		Package depth	775 mm
		Package height	191 mm
		Package weight	25.4 kg
		Packaging data	
		Rack mount kit	✓
		Cables included	RS-232, USB cable
		Manual	✓
		Software CD	✓
		Logistics data	
		Products per pallet	8 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Interface	DB-9 RS-232, SmartSlot, USB
		Input connection type	IEC-320 C14
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304123897



731304123897

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.