TP-Link TL-SG108PE Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : TP-Link

Tuotteen nimi : TL-SG108PE

Tuotekoodi: TL-SG108PE V2

TP-Link TL-SG108PE. Kytkin tyyppi: Hallittu, Kytkinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. MAC-osoitetaulukko: 4000 entries, Kytkentäkapasiteetti: 16 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Power over Ethernet -tuki

Management features

Switch type *	Managed
Switch layer	L2
Quality of Service (QoS) support	✔
Web-based management	✔

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	8
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	8

Network

Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support *	✖
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6
Port mirroring	✔
Link aggregation	✔
Broadcast storm control	✔
Auto MDI/MDI-X	✔
Auto-negotiation	✔
VLAN support	✔
Virtual LAN features	Port-based VLAN
Number of VLANs	32

Data transmission

Switching capacity *	16 Gbit/s
Forwarding rate	11.9 Mpps
MAC address table *	4000 entries
Store-and-forward	✔
Jumbo frames support	✔
Jumbo frames	15000

Power

Power source *	DC
Power supply included *	✔
Input current	1.25 A
Input voltage	48 V
Power consumption (max)	65.2 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✔
Power over Ethernet (PoE) ports quantity	4
Power over Ethernet (PoE) power per port	15.4 W
Total Power over Ethernet (PoE) budget	64 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 95%
Heat dissipation	256.19 BTU/h

Weight & dimensions

Width	158 mm
Depth	101 mm
Height	25 mm

Packaging content

Cables included	AC
User guide	✔

Packaging data

Package type	Box
Package width	131 mm
Package depth	196 mm
Package height	121 mm
Package weight	890 g

Data transmission		Certificates	
Packet buffer memory	1.5 MB	Certification	FCC, CE, RoHS
Security		**Logistics data**	
IGMP snooping	✔	Harmonized System (HS) code	85176990
Loop protection	✔		
Design			
Product colour	Black		
LED indicators	Activity, Link, PoE, Power, Speed, Status		

6935364094744

0845973094744

845973094744

6935364094751