TP-Link TL-SG105E Hallittu L2 Gigabit Ethernet (10/100/1000) musta



Tuotemerkki : TP-Link

Tuotekoodi: TL-SG105E V5

Tuotteen nimi : TL-SG105E

TP-Link TL-SG105E. Kytkin tyyppi: Hallittu, Kytkinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. MAC-osoitetaulukko: 2000 entries, Kytkentäkapasiteetti: 10 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x

Management features	
Switch type *	Managed
Switch layer	L2
Quality of Service (QoS) support	✔
Web-based management	✔
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	5
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	5
Network	
Networking standards *	IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
10G support *	✘
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10BASE-T
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6
Port mirroring	✔
Link aggregation	✔
Auto MDI/MDI-X	✔
Auto-negotiation	✔
VLAN support	✔
Virtual LAN features	Port-based VLAN
Number of VLANs	32
Data transmission	
Switching capacity *	10 Gbit/s
Forwarding rate	7.44 Mpps
MAC address table *	2000 entries
Store-and-forward	✔
Jumbo frames support	✔
Jumbo frames	16000
Packet buffer memory	1 MB
Security	
IGMP snooping	✔
Design	
Product colour	Black

Design	
LED indicators	✔
Performance	
Compatible operating systems	Microsoft Windows XP, Vista Windows 7, Windows 8, MAC OS, NetWare, UNIX / Linux
Power	
Power source *	DC
Power supply included *	✔
Input current	0.6 A
Input voltage	5 V
Power consumption (max)	2.82 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✘
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	9.07 BTU/h
Weight & dimensions	
Width	100 mm
Depth	98 mm
Height	25 mm
Packaging content	
Cables included	AC
Quick start guide	✔
User guide	✔
Rack mount kit	✔
Packaging data	
Package type	Box
Package width	125 mm
Package depth	128 mm
Package height	92 mm
Package weight	450 g
Certificates	
Certification	FCC, CE, RoHS

6935364022044

0845973022037

845973022037

6935364022037

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-DEC-2024. Prints or copies of Information are only valid on the printed Publication date