TP-Link TL-SG1024D Hallitsematon Gigabit Ethernet (10/100/1000) Harmaa

Tuotemerkki : TP-Link

Tuotteen nimi : TL-SG1024D

Tuotekoodi: TL-SG1024D V6

TP-Link TL-SG1024D. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 48 Gbit/s. Verkkostandardit: IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Virtaliitin: DC-tulo jakkiliitin. Telineasennus

Management features

Switch type *	Unmanaged
Quality of Service (QoS) support	✔

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	24
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	24
Power connector	DC-in jack

Network

Networking standards *	IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
10G support *	✘
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Full duplex	✔
Flow control support	✔
Auto MDI/MDI-X	✔
Auto-negotiation	✔

Data transmission

Supported data transfer rates	10/100/100 Mbps
Switching capacity *	48 Gbit/s
Forwarding rate	35.7 Mpps
MAC address table *	8000 entries
Store-and-forward	✔
Maximum data transfer rate	1 Gbit/s
Jumbo frames support	✔
Jumbo frames	10000

Protocols

Supported network protocols	CSMA/CD, TCP/IP

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	13.62 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✘

Other features

Dimensions (WxDxH)	294 x 180 x 44 mm
Connectivity technology	Wired
Bandwidth	48 Gbit/s
Power requirements	100 - 240V, 50/60Hz
Networking features	Gigabit Ethernet
Connectivity LEDs	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Operating temperature (T-T)	32 - 104 °F
Heat dissipation	46.44 BTU/h

Weight & dimensions

Width	294 mm
Depth	180 mm
Height	44 mm

Packaging content

Cables included	AC
User guide	✔
Rack mount kit	✔

Packaging data

Package type	Box
Package width	250 mm

Design

Rack mounting *	✔
Stackable *	✔
Product colour	Grey
LED indicators	✔

Power

Power source *	AC
Power supply included *	✔

Packaging data

Package depth	400 mm
Package height	80 mm
Package weight	1.95 kg

Certificates

Certification	FCC, CE, RoHS

Logistics data

Harmonized System (HS) code	85176990

8459730206206

6935364020620