

TP-Link TL-SG1016D Hallitsematon Gigabit Ethernet (10/100/1000) musta

Tuotemerkki: TP-Link Tuotekoodi: TL-SG1016D V7

Tuotteen nimi: TL-SG1016D



TP-Link TL-SG1016D. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 16. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 32 Gbit/s. Verkkostandardit: IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Virtaliitin: AC-in-liitin. Telineasennus




Management features		Performance	
Switch type *	Unmanaged	Fanless	✓
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	10	Power source * Power supply included *	AC ✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	AC input voltage	100 - 240 V
Gigabit Ethernet (copper) ports quantity	16	AC input frequency Power consumption (max)	50/60 Hz 9.26 W
Power connector	AC-in jack	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	×
Networking standards *	IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Operational conditions	
10G support *	X	Operating temperature (T-T)	0 - 40 °C
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-TX, 1000BASE-T	Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 70 °C 10 - 90%
Cable types supported	Cat3, Cat4, Cat5, Cat5e	Storage relative humidity (H-H)	5 - 90%
Full duplex	✓	Heat dissipation	31.6 BTU/h
Flow control support	✓	Weight & dimensions	
Auto MDI/MDI-X	✓	Width	294 mm
Auto-negotiation	✓	Depth	180 mm
Data transmission		Height	44 mm
Switching capacity *	32 Gbit/s	Packaging content	
Forwarding rate	23.8 Mpps	Cables included	AC
MAC address table *	8000 entries	User guide	✓
Store-and-forward	✓	Rack mount kit	✓
Jumbo frames support	✓	Packaging data	
Jumbo frames	10000	Package type	Box
Protocols		Package width	250 mm
Supported network protocols	CSMA/CD, TCP/IP	Package depth	400 mm
Design		Package height	80 mm
Rack mounting *	/	Package weight	1.85 kg
Nack mounting	•		

Design		Sustainability	
Stackable *	✓	Sustainability compliance	✓
Product colour	Black	Certificates	
LED indicators Performance	/	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
	Microsoft Windows	Logistics data	
Compatible operating systems	2000/XP/2003/Vista/2008/7/2012/8/10 MacOS NetWare UNIX Linux	Harmonized System (HS) code	85176990
Maximum cable length	100 m		











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.