

TP-Link TL-MR3420 langaton reititin Nopea Ethernet Yksi kaista (2,4 GHz) musta, Valkoinen

Tuotemerkki: TP-Link Tuotekoodi: TL-MR3420 V5

Tuotteen nimi: TL-MR3420

TP-Link TL-MR3420. WAN -liitintyyppi: RJ-45. Wi-Fi-taajuus: Yksi kaista (2,4 GHz), Wi-Fi-standardi: Wi-Fi 4 (802.11n), WLAN-tiedonsiirtonopeus (maks.): 300 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Nopea Ethernet, Ethernet LAN -datanopeudet: 10,100 Mbit/s, Verkkostandardit: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3u. Tuotetyyppi: Pöytäreititin, Tuotteen väri: musta, Valkoinen. Sisältää johdot: LAN (RJ-45)





WAN connection		Protocols	
Ethernet WAN *	✓	DHCP client	✓
DSL WAN *	×	DHCP server	✓
SIM card slot *	×	Universal Plug and Play (UPnP)	✓
3G/4G USB modem compatibility *	1	Design	
WAN connection type	RJ-45	Product colour	Black, White
Wireless LAN features		On/off switch	✓
Wi-Fi band *	Single-band (2.4 GHz) Wi-Fi 4 (802.11n) 300 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n) 16-QAM, 64-QAM, CCK, DBPSK, DQPSK, OFDM	Product type *	Tabletop router
Top Wi-Fi standard *		Packaging content	
WLAN data transfer rate (max) * Wi-Fi standards		Cables included AC adapter included	LAN (RJ-45) ✓
Modulation		Quick installation guide	<i>'</i>
Network		Antenna	
Ethernet LAN * Ethernet LAN interface type * Ethernet LAN data rates	Fast Ethernet 10,100 Mbit/s IEEE 802.11b, IEEE 802.11g, IEEE	Antenna design * Antenna gain level (max) Antennas quantity Transmit power	External 3 dBi 2 20 dBmW
Networking standards	802.11n, IEEE 802.3u	Power	20 42
Port forwarding Port triggering Dynamic DNS (DDNS)	* * *	Power source type * Output voltage Output current	DC 12 V 1 A
Number of guest networks (2.4 GHz)	1	Operational conditions	
Wireless Distribution System (WDS) bridge	*	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -40 - 70 °C 10 - 90% 5 - 95%

Network		Weight & dimensions	
Receiver sensitivity	270M: -68dBm@10% PER, 130M: -68dBm@10% PER, 108M: -68dBm@10% PER, 54M: -68dBm@10% PER, 11M: -85dBm@8% PER, 6M: -88dBm@10% PER, 1M: -90dBm@8% PER	Width Depth Height	203.8 mm 138.2 mm 44 mm
		Packaging data	
		Package width	315 mm
Ports & interfaces		Package depth	240 mm
Ethernet LAN (RJ-45) ports *	4	Package height	70 mm
USB port *	✓	Package weight	660 g
USB 2.0 ports quantity	1	Other features	
DC-in jack	✓	USB ports quantity	1
Management features		Dimensions (WxDxH) Power requirements	174 x 111 x 30 mm 9VDC / 0.85A
Wi-Fi Multimedia (WMM)/(WME)	✓	Interface	USB 2.0
Reset button	✓	Bandwidth	2.4 GHz
WPS push button	✓	xDSL connection	x
Security			
Firewall	✓		
Parental control	✓		
DMZ support	✓		
Network address translation (NAT)	✓		

