



## TP-Link 300Mbps Wireless N WiFi Router

**Brand :** TP-Link

**Product code:** TL-WR841N V14

**Product name :** 300Mbps Wireless N WiFi Router

- Performance: 300Mbps wireless speed ideal for interruption sensitive applications like HD video streaming
  - Guest Network: provides separate access for guests while securing the home network
  - IPv6: compatible with IPv6 (Internet Protocol version 6)
  - WPS button: easy wireless security encryption at a push of WPS button
  - IPTV: supports IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming
  - Bandwidth Control: assigns your preferred devices with more bandwidth
  - Parental Controls: manage when and how connected devices can access the internet
- 1x 10/100 Mbps WAN, 4x 10/100 Mbps LAN, IEEE 802.11n/b/g 2.4 GHz, 2.4 GHz: 300 Mbps (802.11n), Single-Core CPU



<b>WAN connection</b>		<b>Design</b>	
Ethernet WAN *	✓	On/off switch	✓
DSL WAN *	✗	Product type *	Tabletop router
SIM card slot *	✗	<b>Certificates</b>	
3G/4G USB modem compatibility *	✗	Certification	CE, FCC, RoHS
<b>Wireless LAN features</b>		<b>Packaging content</b>	
Wi-Fi band *	Single-band (2.4 GHz)	Cables included	LAN (RJ-45)
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)	AC adapter included	✓
WLAN data transfer rate (max) *	300 Mbit/s	Quick start guide	✓
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	<b>Antenna</b>	
<b>Network</b>		Antenna design *	External
Ethernet LAN *	✓	Antenna gain level (max)	5 dBi
Ethernet LAN interface type *	Fast Ethernet	Antennas quantity	2
Ethernet LAN data rates	10,100 Mbit/s	Detachable antenna(s)	✗
Cabling technology	10/100Base-T(X)		270M: -70dBm@10% PER 130M: -74dBm@10% PER 108M: -74dBm@10% PER 54M: -77dBm@10% PER 11M: -87dBm@8% PER 6M: -90dBm@10% PER 1M: -98dBm@8% PER
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3u	Receive power	
Full duplex	✓	Transmit power	20 dBmW
Port forwarding	✓	<b>Power</b>	
Port triggering	✓	Power source type *	DC
Dynamic DNS (DDNS)	✓	Output voltage	9 V
VPN Passthrough	✓	Output current	0.6 A
VPN support	PPTP, L2TP, IPSec	Power consumption (typical)	8 W
<b>Mobile network</b>		<b>Operational conditions</b>	
3G	✗		
4G	✗		

<b>Ports &amp; interfaces</b>		<b>Operational conditions</b>	
Ethernet LAN (RJ-45) ports *	4	Operating temperature (T-T)	0 - 40 °C
USB port *	✗	Storage temperature (T-T)	-40 - 70 °C
Memory card slot(s)	✗	Operating relative humidity (H-H)	10 - 90%
DC-in jack	✓	Storage relative humidity (H-H)	5 - 90%
<b>Management features</b>		<b>System requirements</b>	
Web-based management	✓	Windows operating systems supported Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 98SE, Windows NT, Windows Vista Business, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Professional, Windows XP Professional x64	
Quality of Service (QoS) support	✓		
Reset button	✓		
<b>Security</b>			
Security algorithms	128-bit WEP, 152-bit WEP, 64-bit WEP, SSID, WPA, WPA-PSK, WPA2, WPA2-PSK, WPS		
Firewall	✓		
Firewall security	SPI		
Stateful Packet Inspection (SPI)	✓		
DoS attack prevention	✓		
Filtering	✓		
MAC address filtering	✓		
DMZ support	✓		
<b>Protocols</b>		Linux operating systems supported	✓
DHCP client	✓	Mac operating systems supported	macOS
DHCP server	✓	<b>Weight &amp; dimensions</b>	
Universal Plug and Play (UPnP)	✓	Width	174 mm
<b>Design</b>		Depth	119 mm
Product colour	Black, White	Height	28 mm
LED indicators	Power, Status, WLAN	Weight	700 g
		<b>Packaging data</b>	
		Package width	288 mm
		Package depth	202 mm
		Package height	86 mm
		Package weight	520 g
		<b>Logistics data</b>	
		Harmonized System (HS) code	85176990
		<b>Other features</b>	
		Mobile network connection	✗
		WLAN data transfer rates supported	11,54,300 Mbit/s
		Input current	0.6 A
		Frequency band	2.4 GHz
		Filtering description	IP, MAC, URL
		Rack mounting	✗
		xDSL connection	✗



9154400036990



0845973051242



845973051242



6935364090586



6935364091170

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.