

TP-Link TL-WR841N langaton reititin Nopea Ethernet Yksi kaista (2,4 GHz) musta, Valkoinen

Tuotemerkki : TP-Link Tuotekoodi: TL-WR841N V14

Tuotteen nimi: TL-WR841N

TP-Link TL-WR841N. Wi-Fi-taajuus: Yksi kaista (2,4 GHz), Wi-Fi-standardi: Wi-Fi 4 (802.11n), WLANtiedonsiirtonopeus (maks.): 300 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Nopea Ethernet, Ethernet LAN -datanopeudet: 10,100 Mbit/s, Kaapelitekniikka: 10/100Base-T(X). Tietoturva-algoritmit: 128-bit WEP, 152-bit WEP, 64-bit WEP, SSID, WPA, WPA-PSK, WPA2, WPA2-PSK, WPS, Palomuurisuojaus: SPI. Tuotetyyppi: Pöytäreititin, Tuotteen väri: musta, Valkoinen, LED-merkkivalot: Teho, Tila, WLAN. Sertifiointi: CE, FCC, RoHS





WAN connection		Design	
Ethernet WAN *	✓	On/off switch	✓
DSL WAN *	×	Product type *	Tabletop router
SIM card slot *	×	Certificates	
3G/4G USB modem compatibility *	x	Certification	CE, FCC, RoHS
Wireless LAN features		Packaging content	
Wi-Fi band *	Single-band (2.4 GHz)	Cables included	LAN (RJ-45)
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)	AC adapter included	✓
WLAN data transfer rate (max) *	300 Mbit/s	Quick start guide	✓
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Antenna	
Network		Antenna design *	External
Ethernet LAN *	✓	Antenna gain level (max)	5 dBi
Ethernet LAN interface type *	Fast Ethernet	Antennas quantity	2
Ethernet LAN data rates	10,100 Mbit/s	Detachable antenna(s)	×
Cabling technology	10/100Base-T(X)		270M: -70dBm@10% PER
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3u		130M: -74dBm@10% PER 108M: -74dBm@10% PER
Full duplex	✓	Receive power	54M: -77dBm@10% PER 11M: -87dBm@8% PER
Port forwarding	✓		6M: -90dBm@10% PER
Port triggering	✓		1M: -98dBm@8% PER
Dynamic DNS (DDNS)	✓	Transmit power	20 dBmW
VPN Passthrough	✓	Power	
VPN support	PPTP, L2TP, IPSec	Power source type *	DC
Mobile network		Output voltage	9 V
3G	×	Output current	0.6 A
4G	×	Power consumption (typical)	8 W
70		Operational conditions	

Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports * USB port * Memory card slot(s) DC-in jack	4 × ×	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90%
Management features		System requirements	
Web-based management Quality of Service (QoS) support Reset button	* * *		Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home
Security			Premium, Windows 7 Home Premium x64, Windows 7
Security algorithms Firewall Firewall security Stateful Packet Inspection (SPI) DoS attack prevention Filtering MAC address filtering DMZ support	128-bit WEP, 152-bit WEP, 64-bit WEP, SSID, WPA, WPA-PSK, WPA2, WPA2-PSK, WPS	Windows operating systems supported	Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 98SE, Windows NT, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Premium, Windows Vista Home Premium, Windows Vista Home Premium, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Protocols DHCP client DHCP server	/		
Universal Plug and Play (UPnP)	✓	Linux operating systems supported Mac operating systems supported	✓ macOS
Design		Weight & dimensions	
Product colour LED indicators	Black, White Power, Status, WLAN	Width Depth Height Weight	174 mm 119 mm 28 mm 700 g
		Packaging data	
		Package width Package depth Package height Package weight	288 mm 202 mm 86 mm 520 g
		Logistics data	
		Harmonized System (HS) code	85176990
		Other features	
		Mobile network connection WLAN data transfer rates supported Input current Frequency band Filtering description Rack mounting	X 11,54,300 Mbit/s 0.6 A 2.4 GHz IP, MAC, URL











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.