

TP-Link 300Mbps Wireless N Travel WiFi Router

Brand: TP-Link Product code: TL-WR802N V4

Product name: 300Mbps Wireless N Travel WiFi Router


300Mbps Wireless N Nano Router, 2.4-2.4835 GHz, 1x Fast Ethernet, USB, White/Blue TP-Link 300Mbps Wireless N Travel WiFi Router. WAN connection type: RJ-45. Wi-Fi band: Single-band (2.4 GHz), Top Wi-Fi standard: Wi-Fi 4 (802.11n), WLAN data transfer rate (max): 300 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Security algorithms: 128-bit WEP, 152-bit WEP, 64-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Product type: Tabletop router, Product colour: Blue, White





	Design	
✓	Product colour	Blue, White
×	LED indicators	✓
×	On/off switch	✓
×	Product type *	Tabletop router
RJ-45	Certificates	
	Certification	CE, FCC, RoHS
Single-band (2.4 GHz)	Packaging content	
Wi-Fi 4 (802.11n)	Manual	✓
•	Quick installation guide	✓
002.110, 002.11g, WI-11 + (002.11ii)	Antenna	
Fast Ethernet 10,100 Mbit/s 10/100Base-T(X) IEEE 802.11b, IEEE 802.11g, IEEE 802.11n PPTP, L2TP, IPSec	Antenna design * Receive power Transmit power Power Power Power source type * Output voltage Output current	Internal 270M: -65dBm@10% PER , 130M: -70dBm@10% PER , 108M: -82dBm@10% PER , 54M: -73dBm@10% PER , 11M: -82dBm@8% PER , 6M: -86dBm@10% PER , 1M: -90dBm@8% PER CE: , <20dBm(2.4GHz) , FCC: , <30dBm DC 5 V 1 A
	Operational conditions	
1	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90%
	X X X RJ-45 Single-band (2.4 GHz) Wi-Fi 4 (802.11n) 300 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n) Fast Ethernet 10,100 Mbit/s 10/100Base-T(X) IEEE 802.11b, IEEE 802.11g, IEEE 802.11n Y Y X X X	X X Droduct colour LED indicators On/off switch Product type * RJ-45 Certificates Certification Single-band (2.4 GHz) Wi-Fi 4 (802.11n) 300 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n) Antenna Antenna Antenna design * Fast Ethernet 10,100 Mbit/s 10/100Base-T(X) IEEE 802.11b, IEEE 802.11g, IEEE 802.11n Y Power PPTP, L2TP, IPSec Power source type * Output voltage Output current X X Operational conditions Operating temperature (T-T) Storage temperature (T-T) 1 Operating relative humidity (H-H) X X Storage relative humidity (H-H) X

Management features		System requirements	
Web-based management	✓	System requirements	Windows 2000, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium,
Reset button	✓		
Security			
Security algorithms Firewall Stateful Packet Inspection (SPI) DoS attack prevention Filtering MAC address filtering IP address filtering DMZ support Protocols DHCP client DHCP server Universal Plug and Play (UPnP)	PSK cket Inspection (SPI) prevention ss filtering filtering t t rt v lug and Play (UPnP)	Windows operating systems supported	Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 Pro, Windows Vista Business, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Professional, Windows XP
		Linux operating systems supported	Professional x64
		Mac operating systems supported	macOS
		Weight & dimensions	
		Width Depth Height	57 mm 57 mm 18 mm
		Packaging data	
		Package width Package depth Package height Package weight	110 mm 109 mm 73.5 mm 240 g
		Other features	
		Mobile network connection WLAN data transfer rates supported Frequency range USB ports quantity Supported WAN type Frequency band Rack mounting xDSL connection	X 11,54,300 Mbit/s 2.4 - 2.4835 GHz 1 IP, Static IP, PPPoE, PPTP, L2TP 2.4 GHz X











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.