



ATEN VE600A-AT-G AV-signaalin jatkaja AV-lähetin ja -vastaanotin
musta

Tuotemerkki : ATEN

Tuotekoodi: VE600A-AT-G

Tuotteen nimi : VE600A-AT-G



ATEN VE600A-AT-G. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Tuetut kaapelityypit: Cat5e. Yhteysteknologia: Langallinen, Video sisään: 1 x DVI-D, Video ulos: 1 x DVI-D. Tehonkulutus (maks.): 2,05 W, Tehonkulutus (lähetin) (max): 1,56 W, Tehonkulutus (vastaanotin) (max): 0,76 W. Paino: 490 g, Vastaanottimen mitat (L x S x K): 56 x 91,3 x 24 mm, Vastaanottimen paino: 170 g. Lukumäärä per pakkaus: 2 kpl, Pakkauksen leveys: 59 mm, Pakkauksen syvyys: 239 mm

Features		Operational conditions	
Type *	AV transmitter & receiver	Storage temperature (T-T)	-20 - 60 °C
Maximum resolution *	1920 x 1200 pixels	Operating relative humidity (H-H)	0 - 80%
Cable types supported	Cat5e	Weight & dimensions	
Maximum transfer distance	60 m	Weight	490 g
Supported video modes	1080i, 1080p	Receiver dimensions (WxDxH)	56 x 91.3 x 24 mm
Supported graphics resolutions	1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	Receiver weight	170 g
Bandwidth	6.75 Gbit/s	Transmitter dimensions (WxDxH)	56 x 91.3 x 24 mm
Bandwidth	225 MHz	Transmitter weight	170 g
HDCP	✓	Packaging data	
Material	Metal	Quantity per pack	2 pc(s)
Impedance	100 Ω	Package width	59 mm
Product colour	Black	Package depth	239 mm
Ports & interfaces		Package height	160 mm
Connectivity technology *	Wired	Package weight	660 g
Ethernet LAN	✓	Packaging content	
RJ-45 input ports	2	AC adapter included	✓
RJ-45 output ports	2	Manual	✓
DVI input ports	2	Grounding wire	✓
DVI output ports	2	Mounting kit	✓
Video in	1 x DVI-D	Technical details	
Video out	1 x DVI-D	Compliance certificates	RoHS
Audio input	1	Logistics data	
Audio output	1	Master (outer) case width	315 mm
Power		Master (outer) case length	490 mm
Power consumption (max)	2.05 W	Master (outer) case height	338 mm
Power consumption (transmitter) (max)	1.56 W	Master (outer) case gross weight	14 kg
Power consumption (receiver) (max)	0.76 W	Master (outer) case net weight	9.8 kg
Operational conditions		Products per master (outer) case	20 pc(s)
Operating temperature (T-T)	0 - 50 °C		



4710423777736

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-APR-2025. Prints or copies of Information are only valid on the printed Publication date