

ZYXEL

Zyxel XGS2210-52 Hallittu L2 Gigabit Ethernet (10/100/1000) 1U musta



Tuotemerkki : Zyxel

Tuotekoodi: XGS2210-52-EU0101F

Tuotteen nimi : XGS2210-52

Zyxel XGS2210-52. Kytкин tyyppi: Hallittu, Kytinkerros: L2. Peruskäytäntö RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 48. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 176 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Telineasennus, Kotelo: 1U

Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Web-based management	✓	Stackable *	✓
Traffic shaping	✓	Form factor	1U
ARP inspection	✓	Product colour	Black
System event log	✓	Safety	LVD, BSMI
	RFC 1066, RFC 1213, RFC 1493, RFC 1643, RFC 1757, RFC 2011, RFC 2233, RFC 2358, RFC 2674, RFC 2819, RFC 2925, RFC 3621, RFC 4022, RFC 4113, RFC 4292, RFC 4293	Electromagnetic compatibility	FCC 15 (A), CE (A), BSMI
MIB support		Performance	
		Noise level	44.15 dB
		Plug and Play	✓
		Mean time between failures (MTBF)	970594 h
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	48	AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	AC input frequency	50 - 60 Hz
SFP+ module slots quantity	4	Power consumption (max)	45 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) *	✗
10G support *	✓	Operational conditions	
Port mirroring	✓	Operating temperature (T-T)	0 - 50 °C
IP routing	✓	Storage temperature (T-T)	-40 - 70 °C
Flow control support	✓	Operating relative humidity (H-H)	10 - 95%
Link aggregation	✓	Storage relative humidity (H-H)	10 - 90%
Broadcast storm control	✓	Heat dissipation	153.3 BTU/h
Rate limiting	✓	Weight & dimensions	
Spanning tree protocol	✓	Width	441 mm
MAC address auto-learning supported	✓	Depth	270 mm
VLAN support	✓	Height	45 mm
Virtual LAN features	Private VLAN, Protocol-based VLAN, Port-based VLAN	Weight	3.86 kg
		Packaging content	
		Cables included	AC
		Rack mount kit	✓
		Packaging data	
		Package width	622 mm
		Package depth	358 mm

Data transmission		Packaging data	
Switching capacity *	176 Gbit/s	Package height	108 mm
Throughput	130.9 Mpps	Package weight	4.92 kg
MAC address table *	16000 entries	Certificates	
Number of queues	8	Certification	RoHS
Jumbo frames support	✓	Logistics data	
Jumbo frames	9000	Harmonized System (HS) code	85176990
Packet buffer memory	1.5 MB		
Security			
DHCP features	DHCP client		
Access Control List (ACL)	✓		
IGMP snooping	✓		
Security algorithms	802.1x RADIUS, SNMP, SSH, SSH-2		
MAC address filtering	✓		
SSH/SSL support	✓		
BPDU filtering/protection	✓		
Authentication	MAC-based authentication		



4718937587902

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date