

DisplayPort™ 1.2 Cable to HDMI™ 2.0 Active Adapter

Male/Male 3M/ 9.84Ft



Product Name

DisplayPort™ 1.2 Cable to HDMI™ 2.0 Active Adapter
Male/Male 3M/9.84 Ft.

Product Series

Accessories

Itemcode


CAC-1073

EAN code

8719214470586

UPC code

841615100767



Description:

The Club 3D CAC-1073 is an active HDMI™ signal converter. The DisplayPort™ 1.2 Cable to HDMI™ 2.0 Active Adapter is the easiest solution for connecting your DisplayPort™ 1.2 enabled Game PC or Laptop to an HDMI™ 2.0 enabled 4K UHD Television, monitor or Projector. The adapter is fully compliant to HDMI™ 2.0 specification allowing for 6Gbps TMDS throughput per channel. The interface in the adapter has three lanes for HDMI data, clock, HPD signal and power, offering a total TMDS throughput of 18Gbps. Supports up to 4K UHD Resolution at 60Hz. The DisplayPort™ 1.2 Cable to HDMI2.0 Active Adapter supports (U)HD resolutions of up to 4K UHD 3840x 2160p @ 60Hz for a clear, sharp picture. The support for 60 frames per second provides exceptionally smooth video or gameplay. Use the adapter to play games, view video or browse the internet from your DisplayPort™ 1.2 enabled device in (Ultra) high- resolution. Supporting up to 8 channels of audio, the adapter provides Ultra High Definition digital audio and video. It is the ideal solution for anyone who wants to enjoy 4K UHD/ 60 game-play but lacks a native HDMI™ 2.0 output in their system configuration.

Features:

- Compliant to DisplayPort™ Specification 1.2 for 1.62Gbps,2.7Gbps and 5.4Gbps per lane. Effective video bandwidth 17.28Gbps
- Compliant to HDMI™ Specification 2.0, data rate up to 6Gbps per TMDS channel. Total throughput 18Gbps
- Supports UHD resolutions up to 3840 x 2160p @ 60Hz and 1080p 3D
- Supports full link training and no link training
- Repeater for HDCP 1.4 and HDCP 2.2
- Supports Multiple Color Formats:
 - RGB 8/10/12 bpc; YCbCr4:4:4, YCbCr4:2:2, YCbCr4:2:0 8/10/12 bpc
 - Supports up to 8-Channel LPCM, compressed audio (AC-3, DTS) and HBR audio formats
 - Supports up to 192Khz audio frame rate and up to 24-bits audio sample size
- Supports AMD GCN cards, Nvidia® Maxwell cards and Intel® HD 4600 series and newer. Not intended for older architectures.
- Supports AMD Eyefinity feature
- Windows™ and Mac OS™ compatible

PRODUCT LINK [CLICK HERE](#)

Disclaimer:

While we endeavor to provide the most accurate, up-to-date information available, the content on this document may be out of date or include omissions, inaccuracies or other errors. Therefore Club 3D does not accept any rights claimed on the content of this document. Please refer to a full overview of our Legacy Terms and Conditions on www.club-3d.com. All other brand names are trademarks or registered trademarks and are the property of their respective owners. All content is subject to change without prior notice.

OS Support:

Apple MAC OS X 10.11, 10.10, 10.9, 10.8, 10.7 ;
Windows 10, 8.1, 7 (32 & 64 bit)

In the box:

- Club 3D DisplayPort™ 1.2 Cable to HDMI™ 2.0 Active Adapter

Input:

- DisplayPort™ 1.2 Male

Output:

- HDMI™ 2.0 Male

Other info:

- Boxsize: 175 x 175x 45 mm.
- Cable Weight: 160 gr.
- Cable Size: 3meters / 9.84feet
- Meets ROHS, FCC, and CE EMI requirements

Input:



Output:

