



APC Smart-UPS X SMX750INC - 750VA, 8x C13 output, USB, expandable runtime, NMC

Brand : APC

Product code: SMX750INC

Product name : APC Smart-UPS X SMX750INC - 750VA, 8x C13 output, USB, expandable runtime, NMC



APC Smart-UPS X SMX750INC - 750VA, 8x C13 output, USB, expandable runtime, NMC
APC Smart-UPS X SMX750INC - 750VA, 8x C13 output, USB, expandable runtime, NMC. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 600 W. AC outlet types: C13 coupler, IEC Jumpers, Power plug: C14 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH



Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	0.75 kVA	Cold start	✓
Output power *	600 W	Design	
Waveform *	Pure sine	Form factor *	Rackmount/Tower
Input operation voltage (min) *	151 V	Rack capacity	2U
Input operation voltage (max) *	302 V	Product colour *	Black
Input frequency *	50/60 Hz	Display type	LED
Output operation voltage (min)	220 V	LED indicators	✓
Output operation voltage (max)	240 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	645 J	Storage temperature (T-T)	-15 - 45 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
Noise level	40 dB	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Web-based management	✓	Certificates	
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Auto-restart	✓	Packaging content	
Temperature voltage compensation	✓	Rack mount kit	✓
Ports & interfaces		Cables included	RS-232, USB cable
AC outlet types	C13 coupler, IEC Jumpers	Quick installation guide	✓
Power plug	C14 coupler	Weight & dimensions	
AC outlets quantity	10 AC outlet(s)	Width	432 mm
USB port	✓	Depth	490 mm
USB 2.0 ports quantity	1	Height	89 mm
Serial interface	✓	Weight	22 kg
Serial interface type	RJ-45	Packaging data	
Serial ports quantity	1	Resource CD	✓
Ethernet LAN (RJ-45) ports	1	Software CD	✓
Cabling technology	10/100Base-T	Package width	589 mm
SmartSlot	✓	Package depth	620 mm
Battery		Package height	246 mm
Battery technology	Sealed Lead Acid (VRLA)		

Battery		Packaging data	
Battery life (max)	5 year(s)	Package weight	26.4 kg
Battery recharge time	3 h	Logistics data	
Hot-swap battery	✓	Products per pallet	8 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	578.01



0731304327745



731304327745

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-APR-2025. Prints or copies of Information are only valid on the printed Publication date