



APC Smart-UPS X, Line Interactive, 750VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, Network card, Extended runtime

Brand : APC

Product code: SMX750INC

Product name : Smart-UPS X, Line Interactive, 750VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, Network card, Extended runtime



Smart-UPS X, Line Interactive, 750VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, Network card, Extended runtime

APC Smart-UPS X, Line Interactive, 750VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, Network card, Extended runtime. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 600 W. AC outlet types: C13 coupler, IEC Jumpers, Power plug: C14 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 490 mm, Height: 89 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	3 h
Output power capacity *	0.75 kVA	Hot-swap battery	✓
Output power *	600 W	Automatic battery test	✓
Waveform *	Pure sine	Cold start	✓
Input operation voltage (min) *	151 V	Design	
Input operation voltage (max) *	302 V	Form factor *	Rackmount/Tower
Input frequency *	50/60 Hz	Rack capacity	2U
Output operation voltage (min)	220 V	Product colour *	Black
Output operation voltage (max)	240 V	Display type	LED
Output frequency	50/60 Hz	LED indicators	✓
Surge energy rating	645 J	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Emergency Power Off (EPO)	✓	Operational conditions	
Noise level	40 dB	Operating temperature (T-T)	0 - 40 °C
Surge protection	✓	Storage temperature (T-T)	-15 - 45 °C
Audible alarm(s)	✓	Operating relative humidity (H-H)	0 - 95%
Web-based management	✓	Storage relative humidity (H-H)	0 - 95%
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Operating altitude	0 - 3000 m
Auto-restart	✓	Non-operating altitude	0 - 15000 m
Temperature voltage compensation	✓	Weight & dimensions	
Ports & interfaces		Width	432 mm
AC outlet types	C13 coupler, IEC Jumpers	Depth	490 mm
Power plug	C14 coupler	Height	89 mm
AC outlets quantity	10 AC outlet(s)	Weight	22 kg
USB port	✓	Package width	589 mm
USB 2.0 ports quantity	1	Package depth	620 mm
Serial interface	✓	Package height	246 mm
Serial interface type	RJ-45	Package weight	26.4 kg
Serial ports quantity	1	Packaging data	
Ethernet LAN (RJ-45) ports	1	Rack mount kit	✓
Cabling technology	10/100Base-T	Cables included	RS-232, USB cable
SmartSlot	✓	Quick installation guide	✓
Battery		Resource CD	✓
Battery technology	Sealed Lead Acid (VRLA)	Software CD	✓
Battery life (max)	5 year(s)	Logistics data	
		Products per pallet	8 pc(s)
		Harmonized System (HS) code	85078000



0731304327745



731304327745

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.