D-Link

D-Link DAP-2680 WLAN-tukiasema 1750 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki : D-Link Tuotekoodi: DAP-2680

Tuotteen nimi: DAP-2680

D-Link DAP-2680. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1750 Mbit/s. Tietoturva-algoritmit: 64-bit WEP, 128-bit WEP, SNMP, SNMPv3, SSH, SSID, SSL/TLS, WPA, WPA-Enterprise, WPA2,.... Power over Ethernet -tuki. Tuotteen väri: Valkoinen






Features		Technical details	
2.4 GHz * 5 GHz * 6 GHz * Maximum data transfer rate * Frequency band Networking standards Transmitting power	X 1750 Mbit/s 2.4 - 2.4835; 5.15 - 5.35; 5.47 - 5.85 GHz IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3at, IEEE 802.3u 26.5 dBmW	Pallet gross weight (air) Master (outer) cases per pallet (air) Products per pallet (air) Pallet gross length Pallet gross width Pallet height (air) Pallet gross weight (sea) Master (outer) cases per pallet (sea) Products per pallet (sea) Pallet height (sea) Shipping (inner) case gross weight	311.4 kg 48 pc(s) 240 pc(s) 110 cm 120 cm 2.06 m 311.4 kg 48 pc(s) 240 pc(s) 2.06 m 6.05 kg
Security		Certificates	
Security algorithms * MAC address filtering Management features	64-bit WEP, 128-bit WEP, SNMP, SNMPv3, SSH, SSID, SSL/TLS, WPA, WPA-Enterprise, WPA2, WPA2- Enterprise	Certification Weight & dimensions Width Depth Height Weight	190 mm 190 mm 44.8 mm 580 g
Web-based management	✓	Packaging data	
Ports & interfaces Ethernet LAN (RJ-45) ports * Power Power over Ethernet (PoE) *	1	Package width Package depth Package height Package weight	205 mm 270 mm 112 mm 1.08 kg
Output voltage	12 V	Operational conditions	
Output current Design Placement * Product colour *	2 A Table, Wall White	Operating relative humidity (H-H) Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H)	10 - 90% 0 - 40 °C -20 - 65 °C 5 - 95%

Design		Logistics data	
LED indicators	Power, Status	Harmonized System (HS) code	85176990
Internal	×		
Antenna			
Antennas quantity	3		
Antenna gain level (max)	4.2 dBi		
Technical details			
Shipping (inner) case length	59.9 cm		
Shipping (inner) case width	29.3 cm		
Shipping (inner) case height	24 cm		
Shipping (inner) case net weight	3.44 kg		
Products per shipping (inner) case	5 pc(s)		













Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.