

GUC211VKIT

Portable Laptop Console Crash Cart Adapter IT Kit (TAA Compliant)



- · Works with Windows and Linux
- Portable Console Crash Cart Adapter (<u>GUC211V</u>)
- DisplayPort to VGA adapter (GDPVGAW6)
- HDMI to VGA adapter (GVC311)
- DVI to VGA adapter (GDVIMVGAF)

Try-and-Buy Program

IT Kit Including: Crash Cart Adapter and DisplayPort, HDMI, DVI to VGA Adapters

IOGEAR's Portable Laptop Console Crash Cart Adapter IT Kit is perfect for any IT professional that requires minimal equipment, flexibility and portability in any situation. This IT kit provides the flexibility to mix and match video adapters to meet any computer's needs, including: DisplayPort, HDMI, DVI and VGA. Unlike our competitors, this all-in-one solution saves money and the hassle of buying compatible video adapters.

Portable Laptop Console Crash Cart Adapter

- Provides direct Laptop-to-Computer desktop access
- Included Adapters: DisplayPort, HDMI and DVI
- VGA resolutions up to 1920x1200 @60Hz
- · Programmable macros and hotkeys
- Plug-N-Play No additional software needed
- Bi-directional file transfer between connected laptop and computer
- Access laptop applications in virtual window without switching windows
- BIOS level access

- Perform OS patching, software installation and diagnostic testing on remote computer
- · Video recording and capture of remote computer*
- Mouse DynaSync[™] automatically synchronizes the laptop and connected computer's mouse movements
- · On-screen virtual keyboard with multi-language support
- Supports Windows® 2000, Window Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10, Windows® 10.1
- Adjust remote computer virtual window resolution
- USB powered
- Hot-Pluggable
- Firmware upgradable

*Requires Java application v1.7.0_75 or later ready from laptop for video recording playback











Requirements

Package Contents

 Laptop: Hardware: USB

> 2.0 Port

Operating Systems:

Windo ws® 2000, Windo ws® Vista,

Windo ws® 7, Windo ws®

8.1, W indow

s® 10 Windo ws Ser

ver® 2008+ Linux

 Target Computer: Hardware:

USB Type

A Port VGA

Port DVI

Port (with

GDVI MVGA

E) HDMI Port (with

GVC3 11) Displa yPort Port

(with GDPV GAW6

Note:

The GUC211V only controls the connected computer through a direct cable connection. The GUC211V supports one-to-one direct KVM console; it cannot be used to control two standalone PCs, as it only

- 1 x USB Type A to USB Mini-B Cable
- 1 x DisplayPort to VGA Adapter
- 1 x HDMI to VGA Adapter
- 1 x DVI to VGA Adapter
- 1 x QSG



desktop access User must know login credential of the connected computer if needed for access

Specifications

Function	GUC211VKIT	Dimensions	GUC211VKIT
Computer Connections		Unit Dimensions	
Direct	1	Height	2.375" (6.03cm)
CPU Connectors		Depth	0.75" (1.91cm)
Monitor	1 x VGA Male (Blue)	Length	2.18" (5.56cm); Mini to Type A USB Cable: 72" (183cm); USB and VGA Cables: 19"
Keyboard & Mouse	1 x USB Type A Male (Black)		(48.26cm)
Console Connectors		Unit Package Dimensions	
Keyboard, Mouse, and Monitor	1 x Mini-USB Female (Black)	Width	4.68" (11.9cm)
Video Resolution	VGA / DisplayPort / HDMI / DVI - 1920x1200 @60Hz	Height	6.29" (16cm)
LEDs	C0001E	Depth	2.3" (5.9cm)
On Line	1 x Blue	Master Carton	
Environment	1 X Dido	Width	9" (22.86cm)
Operation Temperature	0~40C	Height	6" (15.24cm)
Storage Temperature	-20~60C	Depth	3" (7.62cm)
Humidity	0~80% RH, Non-condensing	Master Carton Qty.	1
Housing	0-00 /0 Terri, Non-condensing	Weight	
Case	Plastic	Master Carton Wt.	0.5lb (0.23kg)
Warranty	3-Year	Unit Pack Wt.	0.39lb (0.18kg)
wanany	J-1001	Unit Wt.	0.56lb (0.25kg)