

## D-Link DGS-1210-10MP verkkokytkin Hallittu L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

**Tuotemerkki :** D-Link

**Tuotekoodi:** DGS-1210-10MP


**Tuotteen nimi :** DGS-1210-10MP

D-Link DGS-1210-10MP. Kytkin tyyppi: Hallittu, Kytinkerros: L2/L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 20 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE.... Power over Ethernet -tuki



Management features		Performance	
Switch type *	Managed	Flash memory	32 MB
Switch layer	L2/L3	Noise level	0 dB
Quality of Service (QoS) support	✓	Firmware upgradeable	✓
Web-based management	✓	Maximum cable length	100 m
ARP inspection	✓	Mean time between failures (MTBF)	1274005 h
System event log	✓	Power	
MIB support	RFC1212, RFC1213, RFC1215, RFC1493, RFC1157, RFC2573, RFC2575, RFC2576, RFC1442, RFC1901, RFC1902, RFC1903, RFC1904, RFC1905, FC1906, RFC1907, RFC1908, RFC2578, RFC3418, RFC271, RFC1757, RFC2819, RFC2021, RFC1398, RFC1643, RFC1650, RFC2358, RFC2665, RFC2674, RFC2618, RFC4022, RFC4113, RFC2389, RFC2620	AC input voltage	100 - 240 V
		AC input frequency	50 - 60 Hz
		Power consumption (max)	152.3 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓
		Power over Ethernet plus (PoE+) ports quantity	8
		Total Power over Ethernet (PoE) budget	130 W
Ports & interfaces		Operational conditions	
Basic switching RJ-45 Ethernet ports quantity *	8	Operating temperature (T-T)	-5 - 50 °C
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Storage temperature (T-T)	-20 - 70 °C
SFP module slots quantity	2	Operating relative humidity (H-H)	0 - 95%
Fiber optic connector	SFP	Storage relative humidity (H-H)	0 - 95%
		Heat dissipation	519.51 BTU/h
Network		Weight & dimensions	
Networking standards *	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Width	330 mm
10G support *	✗	Depth	180 mm
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Height	44 mm
Cable types supported	Cat5, Cat5e	Weight	1.77 kg
Port mirroring	✓	Packaging data	
Full duplex	✓	Package width	319 mm
Flow control support	✓	Package depth	400 mm
Link aggregation	✓	Package height	91 mm
		Package weight	3.1 kg
		Technical details	
		Shipping (inner) case height	34.9 cm
		Shipping (inner) case width	29.4 cm
		Shipping (inner) case length	41.6 cm

Network		Technical details	
Broadcast storm control	✓	Shipping (inner) case net weight	9.31 kg
Auto MDI/MDI-X	✓	Products per shipping (inner) case	3 pc(s)
Spanning tree protocol	✓	Pallet gross weight (air)	268.3 kg
Head-of-line (HOL) blocking	✓	Master (outer) cases per pallet (air)	24 pc(s)
VLAN support	✓	Products per pallet (air)	72 pc(s)
Number of VLANs	4094	Pallet gross length	110 cm
<b>Optical fiber</b>		Pallet gross width	120 cm
Fiber ethernet cabling technology	100BASE-FX, 1000BASE-X	Pallet height (air)	118.2 cm
<b>Data transmission</b>		Pallet gross weight (sea)	430.6 kg
Switching capacity *	20 Gbit/s	Master (outer) cases per pallet (sea)	40 pc(s)
Forwarding rate	14.88 Mpps	Products per pallet (sea)	120 pc(s)
MAC address table *	8000 entries	Pallet height (sea)	188 cm
Store-and-forward	✓	Shipping (inner) case gross weight	10.1 kg
Jumbo frames support	✓	<b>Certificates</b>	
Jumbo frames	10000	Certification	CE A, VCCI A, FCC A, BSMI, CCC
Packet buffer memory	4.1 MB	<b>Logistics data</b>	
<b>Security</b>		Harmonized System (HS) code	85176990
DHCP features	DHCP server, DHCP client		
Access Control List (ACL)	✓		
Access Control List (ACL) rules	768		
IGMP snooping	✓		
Security algorithms	802.1x RADIUS, EAP, MD5, PEAP, SNMP, SSH-2, SSL/TLS, TTLS		
Loop protection	✓		
IP-MAC-Port binding	✓		
<b>Multicast features</b>			
Multicast support	✓		
<b>Design</b>			
Product colour	Black		
LED indicators	Activity, Link, Power, Speed		
Safety	CB, UL, BSMI, CCC		
<b>Performance</b>			
Memory type	DDR3-SDRAM		
Internal memory	128 MB		



0790069432507



790069432507

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.