

Epson TM-H6000V-234 180 x 180 DPI Wired & Wireless Dot matrix POS printer

Brand : Epson

Product code: C31CG62234

Product name : TM-H6000V-234



- Integrated point-of-sale printer: Capable of receipt printing, slip printing and cheque processing
- Boost efficiency: Fast prints speeds up to 350mm/s¹, cheque processing and auto-cutter
- Flexible connectivity: Built-in USB and Ethernet in all models
- An investment for the future: ePOS-Print, ePOS-display and NFC
- Great value: Low total cost of ownership

180 x 180DPI, 350mm/sec, NFC, USB 1.1, USB 2.0, Ethernet, Serial, Black

Epson TM-H6000V-234. Print technology: Dot matrix, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm, Maximum paper size (slip): 230 x 297 mm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B, Serial interface type: RS-232. Sound pressure level (printing): 55 dB, Sound pressure level (standby): 55 dB, Mean time between failures (MTBF): 180000 h. Product colour: Black

Printing		Features	
Colour	✘	Certification	CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, Directive 2014/30/EU
Maximum resolution	180 x 180 DPI		
Print speed	5.7 lps		
Print speed	350 mm/sec		
Print speed (receipt)	350 mm/sec		
Character size	1.24 x 3.11 mm		
Character density	17.8 cpi		
Printing characters	Text, Graphic, Barcode	Design	
Character sets	ANK	Product colour *	Black
Print technology *	Dot matrix	Power	
Type *	POS printer	AC input voltage	24 V
Paper handling		Operational conditions	
Maximum roll diameter	8.3 cm	Operating temperature (T-T)	5 - 45 °C
Supported paper width	80 mm	Storage temperature (T-T)	-10 - 50 °C
Maximum paper size (slip)	230 x 297 mm	Operating relative humidity (H-H)	10 - 90%
Ports & interfaces		Storage relative humidity (H-H)	10 - 90%
USB port *	✓	System requirements	
USB connector	USB Type-A / USB Type-B	Pre-installed software	Server Direct Print, ePOS-Display, ePOS-Print
Serial interface *	✓	Weight & dimensions	
Serial interface type	RS-232	Width	186 mm
Connectivity technology *	Wired & Wireless	Depth	278 mm
Near Field Communication (NFC)	✓	Height	181 mm
Standard interfaces	Ethernet, NFC, RS-232, USB 1.1, USB 2.0	Weight	4.4 kg
Network		Packaging data	
Ethernet LAN *	✓	Quantity per pack	1 pc(s)
Features		Package width	295 mm
Sound pressure level (printing)	55 dB	Package depth	382 mm
Sound pressure level (standby)	55 dB	Package height	285 mm
Mean time between failures (MTBF)	180000 h	Package weight	5.83 kg
Cutter	✓	Packaging content	
Half-cutter	✓	AC adapter included	✓
Autocutter durability	3 million cuts	Print technology	
Built-in MICR	✓	Column capacity	45 cps / 60 cps
Paper save function	✓	Logistics data	
Print head life	200 km	Harmonized System (HS) code	84433210
Country of origin	China	Products per pallet	56 pc(s)
		Products per pallet layer	8 pc(s)

Features		Logistics data	
Maximum number of copies (endorsement)	2 copies	Pallet gross width	80 cm
Maximum number of copies (slip)	3 copies	Pallet gross length	120 cm
Printer receipt unit life	20000000 lines	Pallet gross height	2.18 m
Printer slip unit life	27000000 lines	Products per pallet (UK)	70 pc(s)
Ribbon life (endorsement)	3 million characters	Products per pallet layer (UK)	10 pc(s)
Ribbon life (slip)	4 million characters	Pallet width (UK)	100 cm
	Middle of Paper pass sensor, Front cover open sensor, Roll paper cover open sensor, Paper End Sensor, Top of Form sensor, Bottom of Form sensor, Slip eject sensor, Receipt near-end sensor	Pallet length (UK)	120 cm
Built-in sensors details		Pallet height (UK)	2.18 m
		Technical details	
		Font size	endorsement: 1.09 mm (W) x 2.41 mm (H)
		Changeable interface	✓
		Other features	
		Buffer size	4 KB
		Mean cycles between failures (MCBF)	65000000
		Print head life	200000000 million characters



8715946651170

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-OCT-2024. Prints or copies of Information are only valid on the printed Publication date