

ZYXEL

Zyxel GS1920-24HPV2 Hallittu Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : Zyxel

Tuotekoodi: GS192024HPV2-EU0101F

Tuotteen nimi : GS1920-24HPV2



Zyxel GS1920-24HPV2. Kytin tyyppi: Hallittu. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 56 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Power over Ethernet -tuki. Telineasennus



Management features		Design	
Switch type *	Managed	Rack mounting *	✓
Quality of Service (QoS) support	✓	Product colour	Black
ARP inspection	✓	LED indicators	✓
System event log	✓	Safety	LVD, BSMI
MIB support	RFC 1066, RFC 1213, RFC 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011.2012,2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819,2925, RFC 3621, RFC 4022, RFC 4113, RFC 4292, RFC 4293	Electromagnetic compatibility	FCC 15 A, CE A, BSMI EMC
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	24	Internal memory	256 MB
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Flash memory	32 MB
Combo SFP ports quantity	4	Noise level	27.2 dB
Fiber optic connector	SFP	Mean time between failures (MTBF)	638691 h
Network		Power	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	AC input voltage	100 - 240 V
10G support *	✗	AC input frequency	50 - 60 Hz
Copper ethernet cabling technology	100BASE-TX, 1000BASE-T	Power consumption (max)	463.5 W
Flow control support	✓	Power over Ethernet (PoE)	
Rate limiting	✓	Power over Ethernet (PoE) *	✓
Spanning tree protocol	✓	Power over Ethernet (PoE) ports quantity	24
VLAN support	✓	Total Power over Ethernet (PoE) budget	375 W
		Operational conditions	
		Operating temperature (T-T)	0 - 50 °C
		Storage temperature (T-T)	-40 - 70 °C
		Operating relative humidity (H-H)	10 - 95%
		Storage relative humidity (H-H)	10 - 95%
		Heat dissipation	1580.54 BTU/h

Network		Weight & dimensions	
Virtual LAN features	Private VLAN, Voice VLAN, Protocol-based VLAN, MAC address-based VLAN, Port-based VLAN, IP subnet-based VLAN	Width	441 mm
		Depth	270 mm
		Height	44 mm
		Weight	3.8 kg
Optical fiber		Packaging content	
Fiber ethernet cabling technology	1000BASE-X	Cables included	AC
		Rack mount kit	✓
Data transmission		Packaging data	
Switching capacity *	56 Gbit/s	Package width	616 mm
Forwarding rate	42 Mpps	Package depth	355 mm
MAC address table *	16000 entries	Package height	107 mm
Packet buffer memory	1.5 MB	Package weight	4.97 kg
Security		Certificates	
DHCP features	DHCP snooping, DHCP relay, DHCPv6 relay, DHCP client	Certification	RoHS
Access Control List (ACL)	✓		
IGMP snooping	✓		
Security algorithms	802.1x RADIUS, SNMP, SNMPv3		
MAC address filtering	✓		
IP-MAC-Port binding	✓		
Authentication	Guest VLAN, Port-based authentication		
Password protection	✓		
Authentication type	IEEE 802.1x, RADIUS		
CPU defense	✓		
Queue scheduling algorithms	SPQ, WFQ, Weighted Round Robin (WRR)		
Multicast features		Logistics data	
Multicast support	✓	Harmonized System (HS) code	85176990



4718937601936

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.