



D-Link DIS-200G-12PS verkkokytkin Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : D-Link

Tuotekoodi: DIS-200G-12PS

Tuotteen nimi : DIS-200G-12PS

D-Link DIS-200G-12PS. Kytkin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 10, Console-portti: RJ-45. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 24 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... DC-syöttöjännite: 46 - 54 V. Power over Ethernet -tuki. Seinäkiinnitteinen, Telineasennus



Management features		Design	
Switch type *	Managed	Safety	UL60950-1
Switch layer	L2	Electromagnetic compatibility	CISPR 22, FCC Part 15B Class A
Quality of Service (QoS) support	✓	Performance	
Web-based management	✓	Mean time between failures (MTBF)	205689 h
Configuring Location Settings (CLI)	✓	Power	
System event log	✓	DC input voltage	46 - 54 V
Ports & interfaces		Power consumption (max)	260 W
Basic switching RJ-45 Ethernet ports quantity *	10	Surge protection	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Surge protection voltage	6 kV
Gigabit Ethernet (copper) ports quantity	10	Power over Ethernet (PoE)	
SFP module slots quantity	2	Power over Ethernet (PoE) *	✓
Console port	RJ-45	Power over Ethernet (PoE) ports quantity	8
Network		Power over Ethernet (PoE) power per port	30 W
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Total Power over Ethernet (PoE) budget	240 W
10G support *	✗	Operational conditions	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Operating temperature (T-T)	-40 - 65 °C
Port mirroring	✓	Storage temperature (T-T)	-40 - 85 °C
Full duplex	✓	Operating relative humidity (H-H)	0 - 95%
Flow control support	✓	Storage relative humidity (H-H)	0 - 95%
Link aggregation	✓	Heat dissipation	887.16 BTU/h
Broadcast storm control	✓	Weight & dimensions	
Auto MDI/MDI-X	✓	Width	171.2 mm
Spanning tree protocol	✓	Depth	48 mm
		Height	210 mm
		Weight	2.5 kg
		Packaging data	
		Package width	217 mm
		Package depth	355 mm

Network		Packaging data	
Active link detection	✓	Package height	76 mm
VLAN support	✓	Package weight	2.2 kg
Virtual LAN features	Voice VLAN, Tagged VLAN, Port-based VLAN	Technical details	
Number of VLANs	4094	Shipping (inner) case height	25.2 cm
Optical fiber		Shipping (inner) case width	37.2 cm
Fiber ethernet cabling technology	1000BASE-X	Shipping (inner) case length	40.9 cm
Data transmission		Shipping (inner) case net weight	11 kg
Switching capacity *	24 Gbit/s	Products per shipping (inner) case	5 pc(s)
Forwarding rate	17.85 Mpps	Pallet gross weight (air)	283.7 kg
MAC address table *	8000 entries	Master (outer) cases per pallet (air)	24 pc(s)
Store-and-forward	✓	Products per pallet (air)	120 pc(s)
Jumbo frames support	✓	Pallet gross length	110 cm
Jumbo frames	9216	Pallet gross width	120 cm
Security		Pallet height (air)	114.3 cm
DHCP features	DHCP client	Pallet gross weight (sea)	496.4 kg
IGMP snooping	✓	Master (outer) cases per pallet (sea)	42 pc(s)
Security algorithms	802.1x RADIUS, SSL/TLS	Products per pallet (sea)	210 pc(s)
Authentication	Port-based authentication	Pallet height (sea)	189.9 cm
DoS attack prevention	✓	Shipping (inner) case gross weight	11.8 kg
Authentication type	RADIUS	Certificates	
Queue scheduling algorithms	SPQ, Weighted Round Robin (WRR)	Certification	CE, FCC, BSMI EN 61000-4-2 ESD EN 61000-4-3 RS EN 61000-4-4 EFT EN 61000-4-5 EN 61000-4-6 CS EN 61000-4-8 IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6
Multicast features		Logistics data	
Multicast support	✓	Harmonized System (HS) code	85176990
Protocols			
Management protocols	SNMP v1/v2c/v3, SNMP, Telnet		
Design			
Rack mounting *	✓		
Stackable *	✗		
Product colour	Black		
Housing material	Metal		
LED indicators	✓		
International Protection (IP) code	IP30		
Wall mountable	✓		
DIN rail mounting	✓		
Number of fans	0 fan(s)		



0790069433504



790069433504

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.