

Data sheet

HP 45W USB-C™ AC Power Adapter



Easy AC charging through USB-C™

Power and charge your notebook or tablet¹ from its USB-C™ port with the HP 45W USB-C™ AC Adapter.

Simple to use

Connect one end of the adapter to the USB-C™ port on your device¹, and plug the AC head into any available wall outlet.

World-class support.

Rest easy with a one-year limited warranty.

¹See Product QuickSpecs for compatibility

Specifications



HP 45W USB-C AC Power Adapter

Model number	V5Y26AA
Dimensions (H x W x D)	66x 66 x 28.5 mm 2.6x2.6x1.1in
Input Efficiency	78.71% min at 115V/230V(option) @5V/2A 87.41% min at 115V/230V(option) @12V/3A 87.73% min at 115V/230V(option) @15V/3A
Input frequency range	47 to 63 Hz
Input AC current	1.4 A at 90 VAC and maximum load
Output power	45W max
DC output	5V/12V/15V
Hold-up time	5msec at 115 VAC input
Output current limit	<5A Over voltage protection: 5V less than 7.25V 12V less than 16.85V 15V less than 20.5V
Connector	3 pin/grounded, mates with type-C connector
Environmental Design	
Operating temperature	0° to 35° C
Non-operating (storage) temperature	-20° to 85° C
Altitude	0 to 5,000 m
Humidity	0% to 95%ww
Storage Humidity	0% to 95%
Safety Certifications	CE Mark - EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; Reliability - failure rate of less than 0.1% annually within the first three years of operation.

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2015 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

