

Delock 2.5" Converter SATA 22 pin / USB 2.0 Type Mini-B > 1 x mSATA / Mini PCIe Slot

Description

This converter by Delock enables the connection of an mSATA SSD in half size or full size format and it can be used as a replacement for 2.5" HDD. Therefore the converter will be connected via the SATA 22 pin interface with your system, optional the power supply can be held by the USB port.

Further, instead of the mSATA SSD, a Mini PCIe module based on USB can be connected and will be integrated to the system via the USB Mini-B port.



Specification

- Connectors:
 - 1 x SATA 6 Gb/s 22 pin plug
 - 1 x USB 2.0 Type Mini-B female
 - 1 x mSATA / Mini PCIe slot (half size / full size)
- Interface Mini PCIe: USB
- Form factor: 2.5"
- Data transfer rate up to 6 Gb/s
- For 3.3 V mSATA module
- Power supply via SATA 15 pin plug or Mini USB female
- Bootable
- Dimensions (LxWxH): ca. 100 x 70 x 7 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux Kernel 3.19
- A free SATA 22 pin interface
- A free USB interface (for Mini PCIe or power supply)

Package content

- Converter
- User manual

Item No. 62853

EAN: 4043619628537

Country of origin: China

Package: Retail Box



Images



General

Form factor:	2.5"
function:	bootable
Supported operating system:	Linux Kernel 3.19 Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit

Interface

connector 1:	1 x SATA 6 Gb/s 22 pin plug
connector 2:	1 x USB 2.0 Type Mini-B female
connector 3:	1 x mSATA / Mini PCIe slot (half size / full size)

Technical characteristics

Data transfer rate:	6 Gb/s
---------------------	--------

Physical characteristics

Length:	100 mm
Width:	70 mm
Height:	7 mm