## Lexmark CX921de Colour 1200 x 1200 DPI A3

**Brand :** Lexmark **Product code:** 32C0012

Product name: CX921de

Lexmark CX921de. Print technology: Laser, Colour. Maximum duty cycle: 150000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A3. Print speed (black, normal quality, A4/US Letter): 35 ppm, Duplex printing. Product colour: Black, Grey

Printing		Performance	
Print speed (colour, normal quality,	35 ppm	Built-in processor	1
A4/US Letter) Colour *	<b>✓</b>	Processor frequency	1200 MHz
Print technology *	Laser	Processor cores	4
Duplex printing *	∠ Lasei	Sound pressure level (printing)	51 dB
Maximum resolution *	1200 x 1200 DPI	Sound pressure level (duplex printing)	53 dB
Print speed (black, normal quality,		Design	
A4/US Letter) *	35 ppm	Product colour *	Black, Grey
Duplex print speed (black, normal quality, A4/US Letter)	35 ppm	Built-in display *	olack, Grey ✓
Time to first page (black, normal)	7 s	Colour display	<b>✓</b>
Time to first page (colour, normal)	7 s	Display diagonal	10.9 cm (4.3")
Features		Touchscreen	✓
Maximum duty cycle * Recommended duty cycle	150000 pages per month 4000 - 20000 pages per month	Control type	Touch ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB
Page description languages *	PCL 5c, PCL 6, PDF 1.7, PPDS, PostScript 3, XPS		
Input & output capacity			Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC,
Total number of input trays * Total input capacity * Total output capacity * Paper input type Maximum number of input trays	3 1150 sheets 250 sheets Paper tray 6	Certification	EUP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL- AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT Gold, Blue Angel (Blauer Engel)
Maximum input capacity	6650 sheets	Power	
Maximum output capacity	3500 sheets	Power consumption (printing) *	575 W
Paper handling		Power consumption (ready)	140 W
Maximum ISO A-series paper size *	A3 Banner, Card stock, Envelopes, Labels, Plain paper	Energy Star Typical Electricity Consumption (TEC)	2.3 kWh/week
Paper tray media types *		System requirements	
ISO A-series sizes (A0A9) *	A3, A4, A5, A6 Executive, Folio, Letter, Oficio,	Windows operating systems supported	✓
Non-ISO print media sizes	Statement, Super Tabloid (media size), Universal, Legal	Mac operating systems supported	✓
JIS B-series sizes (B0B9)	B4	Linux operating systems supported	✓
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Operational conditions	
Photo paper sizes (imperial)	4x6"	Operating temperature (T-T)	10 - 40 °C
Paper tray media weight	60 - 256 g/m²	Operating relative humidity (H-H)	15 - 85%
Ports & interfaces		Operating altitude	0 - 2500 m
Standard interfaces	Ethernet, USB 2.0	Sustainability	
USB connector	USB Type-A / USB Type-B	Sustainability certificates	Blue Angel, ENERGY STAR
Optional connectivity	Serial (RS-422), Wireless LAN	Weight & dimensions	
Network		Width	615 mm
Ethernet LAN *	✓	Depth	693 mm
Cabling technology	10/100/1000Base-T(X)	Height	780 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Weight	88.5 kg

Network		Packaging data		
Security algorithms	HTTPS, IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMP, SSL/TLS, TTLS	Package width Package depth	758 mm 911 mm	911 mm
Mobile printing technologies	Apple AirPrint	Package height Package weight	1057 mm 103 kg	
Performance		3 3	J	
Internal memory * Maximum internal memory	1024 MB 3072 MB			

