Lexmark CX923dxe Laser A3 1200 x 1200 DPI 55 ppm

Brand : Lexmark **Product code:** 32C0239

Product name: CX923dxe

Lexmark CX923dxe. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200×1200 DPI, Print speed (colour, normal quality, A4/US Letter): 55 ppm. Copying: Colour copying. Scanning: Colour scanning, Optical scanning resolution: 600×600 DPI. Faxing: Colour faxing. Maximum ISO Aseries paper size: A3. Product colour: Black, White







Printing		Ports & interfaces	
Print technology *	Laser	USB connector	USB Type-A / USB Type-B
Printing *	Colour printing	Network	
Duplex printing *	✓	Ethernet LAN *	1
Maximum resolution *	1200 x 1200 DPI	Cabling technology	10/100/1000Base-T(X)
Print speed (black, normal quality, A4/US Letter) *	55 ppm	Ethernet LAN data rates	10,100,1000 Mbit/s
Print speed (colour, normal quality, A4/US Letter)	55 ppm	Security algorithms	IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, TTLS
Duplex print speed (black, normal quality, A4/US Letter)	55 ppm	Supported network protocols (IPv4) Supported network protocols (IPv6)	TCP/IP TCP/IP
Time to first page (black, normal)	5 s	Mobile printing technologies	Apple AirPrint
Time to first page (colour, normal)	5 s	Performance	
Copying		Maximum internal memory	4096 MB
Copying *	Colour copying	Internal memory *	2048 MB
Copy speed (black, normal quality,	55 cpm	Built-in processor	✓
A4)	33 cp.11	Processor frequency	1200 MHz
Copy speed (colour, normal quality, A4)	55 cpm	Processor cores	4
Time to first copy (black, normal)	4.9 s	Sound pressure level (printing)	52 dB
Time to first copy (colour, normal)	5.8 s	Sound pressure level (duplex	54 dB
Copier resize	25 - 400%	printing) Sound pressure level (copying)	56 dB
Scanning		Sound pressure level (scanning)	53 dB
Duplex scanning *	1	Sound power level (standby)	29 dB
Scanning *	Colour scanning	Design	
Optical scanning resolution *	600 x 600 DPI	Product colour *	Black, White
Maximum scan area	297 x 432 mm	Market positioning *	Business
Scanner type *	Flatbed & ADF scanner	Built-in display *	✓
Scan technology	CCD	Display diagonal	25.4 cm (10")
Scan to	E-mail, FTP, USB	Touchscreen	1
Scan speed (colour)	80 ppm	Control type	Touch
Scan speed (black)	80 ppm	Colour display	✓
Duplex scan speed (colour)	160 ppm	Power	
Duplex scan speed (black)	160 ppm	Power consumption (printing)	1075 W
Image formats supported Document formats supported	JPG, TIF PDF, XPS	Power consumption (copying)	1100 W
	rui, xr3	Power consumption (scanning)	250 W
Fax		Power consumption (ready)	230 W
Faxing *	Colour faxing	Power consumption (sleep)	2.9 W
Fax transmission speed Modem speed	3 sec/page 33.6 Kbit/s	Energy Star Typical Electricity Consumption (TEC)	4.6 kWh/week
Features			
Recommended duty cycle	7000 - 50000 pages per month		
necommended daty cycle	7000 - 30000 pages per mondi		

Features		System requirements	
Maximum duty cycle * Printing colours *	250000 pages per month Cyan, Magenta, Yellow	Windows operating systems supported	✓
Input & output capacity		Mac operating systems supported Linux operating systems supported	1
Total input capacity * Total output capacity * Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input	3 3650 sheets 250 sheets Paper tray ✓ 100 sheets 4 6650 sheets 3500 sheets A3 Banner, Card stock, Envelopes,	Operational conditions	
		Operating relative humidity (H-H) Operating temperature (T-T) Operating altitude	15 - 85% 10 - 30 °C 0 - 2500 m
		Certificates	
Maximum number of input trays Maximum input capacity Maximum output capacity		Certification	ICES-003 A, BSMI A, VCCI A, FCC A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB, ISO-532B, CE (EU) DoC, EFTA (CE), KC, CCC, C-tick DoC, Eup, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT
Paper handling Maximum ISO A-series paper size * Paper tray media types *			
ISO A-series sizes (A0A9) *	Labels, Plain paper A3, A4, A5, A6	Sustainability	
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal 7 3/4, 9, 10, B5, C5, DL 60 - 256 g/m ²	Sustainability certificates	Blue Angel, ENERGY STAR
Envelopes sizes		Weight & dimensions	
Paper tray media weight Multi-Purpose Tray media weight		Width Depth Height	615 mm 697 mm 1225 mm
Ports & interfaces		Weight	134.5 kg
Standard interfaces USB port	Ethernet, USB 2.0 ✓	Packaging data	
		Package width Package depth Package height Package weight	758 mm 911 mm 1505 mm 168 kg

