

## Lexmark CX924dxe Laser A3 1200 x 1200 DPI 65 ppm

**Brand :** Lexmark

**Product code:** 32C0241

**Product name :** CX924dxe

Lexmark CX924dxe. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200 x 1200 DPI, Print speed (colour, normal quality, A4/US Letter): 65 ppm. Copying: Colour copying. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Colour faxing. Maximum ISO A-series paper size: A3. Direct printing. Product colour: Black, Grey

<b>Printing</b>		<b>Ports &amp; interfaces</b>	
Print technology *	Laser	Standard interfaces	Ethernet, USB 2.0
Printing *	Colour printing	Direct printing *	✓
Duplex printing *	✓	USB port	✓
Maximum resolution *	1200 x 1200 DPI	USB connector	USB Type-A / USB Type-B
Print speed (black, normal quality, A4/US Letter) *	65 ppm	Optional connectivity	Serial (RS-422), Wireless LAN
Print speed (colour, normal quality, A4/US Letter)	65 ppm	<b>Network</b>	
Duplex print speed (ISO/IEC 24734) mono	65 ipm	Ethernet LAN *	✓
Time to first page (black, normal)	4.9 s	Cabling technology	10/100/1000Base-T(X)
Time to first page (colour, normal)	4.9 s	Ethernet LAN data rates	10,100,1000 Mbit/s
<b>Copying</b>		Security algorithms	HTTPS, IPsec, LEAP, MD5, MSCHAPv2, PEAP, SSL/TLS, TTLS
Copying *	Colour copying	Mobile printing technologies	Apple AirPrint
Copy speed (black, normal quality, A4)	65 cpm	<b>Performance</b>	
Copy speed (colour, normal quality, A4)	65 cpm	Maximum internal memory	4096 MB
Time to first copy (black, normal)	4.8 s	Internal memory *	2048 MB
Time to first copy (colour, normal)	5.5 s	Built-in processor	✓
Copier resize	25 - 400%	Processor frequency	1200 MHz
<b>Scanning</b>		Processor cores	4
Duplex scanning *	✓	Sound pressure level (printing)	55 dB
Scanning *	Colour scanning	Sound pressure level (duplex printing)	55 dB
Optical scanning resolution *	600 x 600 DPI	Sound pressure level (copying)	57 dB
Maximum scan area	297 x 432 mm	Sound pressure level (scanning)	53 dB
Scanner type *	Flatbed & ADF scanner	Sound pressure level (quiet mode)	50 dB
Scan technology	CCD	Sound power level (standby)	28 dB
Scan to	E-mail, FTP, PC, USB	<b>Design</b>	
Scan speed (colour)	80 ppm	Product colour *	Black, Grey
Scan speed (black)	80 ppm	Market positioning *	Business
Duplex scan speed (colour)	160 ppm	Built-in display *	✓
Duplex scan speed (black)	160 ppm	Display diagonal	6.35 cm (2.5")
Image formats supported	JPEG XR, JPG, TIF	Touchscreen	✓
Document formats supported	PDF, XPS	Control type	Touch
<b>Fax</b>		Colour display	✓
Faxing *	Colour faxing	<b>Power</b>	
Fax transmission speed	3 sec/page	Power consumption (printing)	1250 W
Modem speed	33.6 Kbit/s	Power consumption (copying)	1275 W
<b>Features</b>		Power consumption (scanning)	250 W
Recommended duty cycle	8000 - 50000 pages per month	Power consumption (ready)	230 W
Maximum duty cycle *	275000 pages per month	Power consumption (sleep)	2.9 W
Page description languages	PCL 5c, PCL 6, PDF 1.7, PPDS, PostScript 3, XPS	Energy Star Typical Electricity Consumption (TEC)	5 kWh/week
		<b>System requirements</b>	
		Windows operating systems supported	✓

<b>Input &amp; output capacity</b>		<b>System requirements</b>	
Total number of input trays *	4	Linux operating systems supported	✓
Total input capacity *	3650 sheets	<b>Operational conditions</b>	
Total output capacity *	250 sheets	Operating relative humidity (H-H)	15 - 85%
Paper input type	Paper tray	Operating temperature (T-T)	10 - 30 °C
Auto document feeder (ADF)	✓	Operating altitude	0 - 2500 m
Auto document feeder (ADF) input capacity	100 sheets	<b>Certificates</b>	
Auto document feeder (ADF) output capacity	100 sheets	Certification	ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECF, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT
Maximum number of input trays	5	<b>Sustainability</b>	
Maximum input capacity	6650 sheets	Sustainability certificates	Blue Angel, ENERGY STAR
Maximum output capacity	3500 sheets	<b>Weight &amp; dimensions</b>	
<b>Paper handling</b>		Width	615 mm
Maximum ISO A-series paper size *	A3	Depth	697 mm
Paper tray media types *	Banner, Card stock, Envelopes, Labels, Plain paper	Height	1225 mm
Multi-purpose tray media types	Envelopes, Labels, Plain paper	Weight	134.5 kg
ISO A-series sizes (A0...A9) *	A3, A4, A5, A6	<b>Packaging data</b>	
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Package width	758 mm
JIS B-series sizes (B0...B9)	B5	Package depth	911 mm
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Package height	1505 mm
Paper tray media weight	60 - 256 g/m <sup>2</sup>	Package weight	168 kg
Multi-Purpose Tray media weight	60 - 256 g/m <sup>2</sup>	<b>Other features</b>	
		Duplex	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date