Lexmark CX924dxe Laser A3 1200 x 1200 DPI 65 ppm

Tuotemerkki : Lexmark Tuotekoodi: 32C0241

Tuotteen nimi: CX924dxe

Lexmark CX924dxe. Tulostustekniikka: Laser, Tulostus: Väritulostus, Suurin resoluutio: 1200 x 1200 DPI, Tulostusnopeus (väri, normaalilaatu, A4/US Letter): 65 ppm. Kopiointi: Värikopiointi. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Faksaus: Värifaksaus. Suurin ISO Aluokan paperikoko: A3. Suoratulostus. Tuotteen väri: musta, Harmaa

Printing		Ports & interfaces	
Print technology *	Laser	Standard interfaces	Ethernet, USB 2.0
Printing *	Colour printing	Direct printing *	✓
Duplex printing *	1	USB port	✓
Maximum resolution *	1200 x 1200 DPI	USB connector	USB Type-A / USB Type-B
Print speed (black, normal quality, A4/US Letter) *	65 ppm	Optional connectivity	Serial (RS-422), Wireless LAN
Print speed (colour, normal quality, A4/US Letter)	65 ppm	Network Ethernet LAN *	✓
Duplex print speed (ISO/IEC 24734) mono	65 ipm	Cabling technology	10/100/1000Base-T(X)
Time to first page (black, normal)	4.9 s	Ethernet LAN data rates	10,100,1000 Mbit/s
Time to first page (colour, normal)	4.9 s	Security algorithms	HTTPS, IPSec, LEAP, MD5, MSCHAPv2, PEAP, SSL/TLS, TTLS
Copying		Mobile printing technologies	Apple AirPrint
Copying *	Colour copying	Performance	
Copy speed (black, normal quality, A4)	65 cpm	Maximum internal memory	4096 MB
Copy speed (colour, normal quality, A4)	65 cpm	Internal memory * Built-in processor	2048 MB ✓
Time to first copy (black, normal)	4.8 s	Processor frequency	1200 MHz
Time to first copy (colour, normal)	5.5 s	Processor cores	4
Copier resize	25 - 400%	Sound pressure level (printing)	55 dB
Scanning		Sound pressure level (duplex printing)	55 dB
Duplex scanning *	✓	Sound pressure level (copying)	57 dB
Scanning *	Colour scanning	Sound pressure level (scanning)	53 dB
Optical scanning resolution *	600 x 600 DPI	Sound pressure level (quiet mode)	50 dB
Maximum scan area	297 x 432 mm	Sound power level (standby)	28 dB
Scanner type *	Flatbed & ADF scanner	Design	
Scan technology	CCD	Product colour *	Black, Grey
Scan to	E-mail, FTP, PC, USB	Market positioning *	Business
Scan speed (colour)	80 ppm	Built-in display *	✓
Scan speed (black)	80 ppm		6.35 cm (2.5")
Duplex scan speed (colour)	160 ppm	Display diagonal	, ,
Duplex scan speed (black)	160 ppm	Touchscreen	✓ To all
Image formats supported	JPEG XR, JPG, TIF	Control type	Touch
Document formats supported	PDF, XPS	Colour display	•
Fax		Power	
Faxing *	Colour faxing	Power consumption (printing)	1250 W
Fax transmission speed	3 sec/page	Power consumption (copying)	1275 W
Modem speed	33.6 Kbit/s	Power consumption (scanning)	250 W
Features		Power consumption (ready)	230 W
Recommended duty cycle	8000 - 50000 pages per month	Power consumption (sleep)	2.9 W
Maximum duty cycle *	275000 pages per month	Energy Star Typical Electricity Consumption (TEC)	5 kWh/week
Page description languages	PCL 5c, PCL 6, PDF 1.7, PPDS, PostScript 3, XPS	System requirements	
		Windows operating systems supported	✓

Input & output capacity		System requirements	
	4		
Total number of input trays * Total input capacity *	4 3650 sheets	Linux operating systems supported	•
Total output capacity *		Operational conditions	
Paper input type	250 sheets Paper tray	Operating relative humidity (H-H)	15 - 85%
Auto document feeder (ADF)	rapei tray ✓	Operating temperature (T-T)	10 - 30 °C
Auto document feeder (ADF) input	•	Operating altitude	0 - 2500 m
capacity	100 sheets	Certificates	
Auto document feeder (ADF) output capacity	100 sheets		ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A,
Maximum number of input trays	5	NOM-032, UL, cUL, NOM, FDA/CDRH, IEC 60825-1,	NOM-032, UL, cUL, NOM, US
Maximum input capacity	6650 sheets		FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE),
Maximum output capacity	3500 sheets	Certification	KC logo, CCC, C-tick DoC, EuP,
Paper handling			CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-
Maximum ISO A-series paper size *	A3		AR, GS Mark, Green Dot, ISO-9296,
Paper tray media types *	Banner, Card stock, Envelopes, Labels, Plain paper		COC, CCD-035 EcoLogo, Green Mark, EPEAT
Multi-purpose tray media types	Envelopes, Labels, Plain paper	Sustainability	
ISO A-series sizes (A0A9) *	A3, A4, A5, A6	Sustainability certificates	Blue Angel, ENERGY STAR
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Weight & dimensions	
JIS B-series sizes (B0B9)	B5	Width	615 mm
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Depth	697 mm
Paper tray media weight	60 - 256 g/m²	Height	1225 mm
Multi-Purpose Tray media weight	60 - 256 g/m²	Weight	134.5 kg
		Packaging data	
		Package width	758 mm
		Package depth	911 mm
		Package height	1505 mm
		Package weight	168 kg
		Other features	
		Duplex	✓

