Lexmark CS622de Colour A4

Brand : Lexmark **Product code:** 42C0091

Product name: CS622de

Lexmark CS622de. Print technology: Laser, Colour. Maximum duty cycle: 100000 pages per month. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 38 ppm, Duplex printing. Product colour: Grey, White

Printing		Performance	
Print resolution colour Print resolution black Print speed (colour, normal quality, A4/US Letter)	2400 x 600 DPI 1200 x 1200 DPI 38 ppm	Processor cores Sound pressure level (printing) Sound pressure level (duplex printing)	2 51 dB 53 dB
Colour *	✓	Design	
Print technology * Duplex printing * Print speed (black, normal quality, A4/US Letter) *	Laser ✓ 38 ppm	Market positioning * Product colour * Built-in display *	Home & office Grey, White ✓
Duplex print speed (black, normal quality, A4/US Letter)	19 ppm	Colour display Display diagonal	10.9 cm (4.3")
Duplex print speed (colour, normal quality, A4/US Letter) Time to first page (black, normal) Time to first page (colour, normal) Print margins (top, bottom, right, left)	19 ppm 7 s 7 s 4.2 mm	Touchscreen Control type	Touch ENERGY STAR, Blue Angel RAL- UZ-171, ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, CUL
Features Maximum duty cycle * Recommended duty cycle Printing colours * Page description languages * Country of origin	100000 pages per month 1500 - 10000 pages per month Black, Cyan, Magenta, Yellow Microsoft XPS, PCL 5c, PCL 6, PDF 1.7, PPDS, PostScript 3 China	Certification	CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DOC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, UCRF, EC 1275
	Cillia	Power	
Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Maximum number of input trays Maximum input capacity Maximum output capacity	2 251 sheets 125 sheets 5 1451 sheets 125 sheets	Power consumption (printing) * Power consumption (ready) Power consumption (standby) Power consumption (off) Energy Star Typical Electricity Consumption (TEC)	570 W 37 W 1.5 W 0.2 W 1.6 kWh/week
Paper handling	125 Silects	System requirements	
Maximum ISO A-series paper size * Paper tray media types * ISO A-series sizes (A0A9) * Non-ISO print media sizes	A4 Card stock, Envelopes, Labels, Plain paper A4, A5, A6 Executive, Folio, Hagaki card, Legal,	Windows operating systems supported Mac operating systems supported Linux operating systems supported Other operating systems supported	
JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight	Letter, Oficio, Statement, Universal B5 7 3/4, 9, 10, C5, DL 90.3 - 105 g/m ²	Operational conditions Operating temperature (T-T) Operating relative humidity (H-H) Operating altitude	10 - 32 °C 8 - 80% 0 - 3048 m
Ports & interfaces		Sustainability	
Standard interfaces Direct printing * USB 2.0 ports quantity USB connector	Ethernet, USB 2.0 ✓ 3 USB Type-A / USB Type-B	Sustainability certificates Weight & dimensions Width Depth	ENERGY STAR 442 mm 421 mm
Optional connectivity	Wireless LAN	-r ··	

Network		Weight & dimensions	
Ethernet LAN *	✓	Height	308 mm
Cabling technology	10/100/1000Base-T(X)	Weight	21 kg
Ethernet LAN data rates	10,100,1000 Mbit/s	Packaging data	
Security algorithms	HTTPS, IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, SSL/TLS, TTLS	Package width Package depth	495 mm 595 mm
Supported network protocols (IPv4)	TCP/IP IPv4, AppleTalk	Package height	402 mm
Supported network protocols (IPv6)	TCP/IP IPv6, TCP, UDP	Package weight	23.9 kg
	DHCP, APIPA (AutoIP), mDNS, IGMP, Bonjour, WINS, DDNS, SNMPv3,	Packaging content	
Management protocols	SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL5/TLS), Finger	Cartridge(s) included Included cartridge capacity (black)	3000 pages
Mobile printing technologies	Apple AirPrint	Included cartridge capacity (CMY)	2000 pages
Performance		Manual Software CD	✓ ✓
Internal memory * Maximum internal memory	1024 MB 1024 MB	Documentation CD	✓
•		Developer unit included	✓
Built-in processor Processor frequency	1000 MHz	Cables included	AC





734646682633

0734646682633

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.