Lexmark MS825dn 1200 x 1200 DPI A4

Brand : Lexmark **Product code:** 50G0321

Product name: MS825dn

Lexmark MS825dn. Print technology: Laser. Maximum duty cycle: 350000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 66 ppm, Duplex printing. Display: LCD, Product colour: Black, White

Printing		Performance	
Colour *	x	Sound pressure level (printing)	58 dB
Print technology *	Laser	Sound pressure level (duplex	58 dB
Duplex printing *	✓	printing)	
Maximum resolution *	1200 x 1200 DPI	Design	
Print speed (black, normal quality, A4/US Letter) *	66 ppm	Product colour * Built-in display *	Black, White
Duplex print speed (black, normal quality, A4/US Letter)	40 ppm	Display	LCD
Time to first page (black, normal)	4 s	Colour display	√
Features		Display diagonal	6.35 cm (2.5")
Maximum duty cycle *	350000 pages per month	Touchscreen	✓ Taurah
Recommended duty cycle	5000 - 100000 pages per month	Control type	Touch
Printing colours *	Black		AL-UZ 205, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA, UL
Page description languages *	Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PPDS, PostScript 3, XHTML		60950-1, FCC Class A, cUL CAN / CSA-C22.2 60950-1, NOM, CB, EN /
Input & output capacity			IEC 60950-1, CB EN / IEC 60825-1, CE DoC (EN 62301 Class A, EN
Total number of input trays *	2	Certification	62311, CE EN / IEC 60950-1, CE EN /
Total input capacity *	650 sheets		IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA
Total output capacity *	550 sheets		(CE), KCC, CCC, CECP, CEL, C-tick
Paper input type	Paper tray		DoC, UL-AR, KC mark, UL GS mark,
Maximum number of input trays	6		EC 1275, MET-I, ISO 532B , ECMA-370, TED, GOST-R, SII, TER
Maximum input capacity	4400 sheets		ECHA 370, 128, 0031 N, 311, 121
Maximum output capacity	2550 sheets	Power	
Paper handling		Power consumption (ready) Power consumption (standby)	38.4 W 0.2 W
Maximum ISO A-series paper size *	A4 Card stock, Envelopes, Labels, Plain paper, Transparencies Envelopes, Executive, Labels, Legal, Letter, Plain paper, Transparencies A4, A5, A6	Energy Star Typical Electricity	O OE KWhanak
Paper tray media types *		Consumption (TEC)	0.95 kWh/week
Multi-purpose tray media types		System requirements	
ISO A-series sizes (A0A9) *		Windows operating systems supported	✓
Non-ISO print media sizes	Executive, Folio, Legal, Letter,	Mac operating systems supported	✓
Non-130 print media sizes	Oficio, Statement, Universal	Linux operating systems supported	✓
JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight	B5 7 3/4, 9, 10, B5, C5, DL 60 - 176 g/m ²	Server operating systems supported	SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, SUSE Linux Enterprise Server 12, Windows 2000 Server
Ports & interfaces		O	WITHOUNS ZOOD SELVEL
Direct printing *	✓	Operational conditions	10. 20.00
USB port *	· ·	Operating temperature (T-T)	10 - 32 °C
USB connector	USB Type-A / USB Type-B	Operating relative humidity (H-H)	8 - 80%
Optional connectivity	Parallel, Wireless LAN	Operating altitude Sustainability	0 - 2896 m
Network		Sustainability certificates	Blue Angel, ENERGY STAR
Ethernet LAN *	✓	·	DIGC Aligel, LINENGT STAN
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Ethernet LAN data rates	10,100,1000 Mbit/s	Width	445 mm
		Depth	510 mm
		Height	428 mm

Network		Weight & dimensions	
Security algorithms	HTTPS, IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMP, SNMPv3, SSL/TLS, TTLS	Weight	25.4 kg
		Packaging data	
Performance		Package width	565 mm
Internal memory *	512 MB	Package depth Package height	650 mm 550 mm 29.9 kg
Maximum internal memory Built-in processor	4608 MB ✓	Package weight	
Processor frequency	1000 MHz		
Processor cores	2		

