

Lexmark MS826de 1200 x 1200 DPI A4

Brand : Lexmark

Product code: 50G0331

Product name : MS826de

Lexmark MS826de. Print technology: Laser. Maximum duty cycle: 350000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 66 ppm, Duplex printing. Display: LCD, Product colour: Black, White

| Printing | | Performance | |
|--|--|---|--|
| Colour * | ✗ | Sound pressure level (printing) | 58 dB |
| Print technology * | Laser | Sound pressure level (duplex printing) | 58 dB |
| Duplex printing * | ✓ | Design | |
| Maximum resolution * | 1200 x 1200 DPI | Product colour * | Black, White |
| Print speed (black, normal quality, A4/US Letter) * | 66 ppm | Built-in display * | ✓ |
| Duplex print speed (black, normal quality, A4/US Letter) | 40 ppm | Display | LCD |
| Time to first page (black, normal) | 4 s | Colour display | ✓ |
| Features | | Display diagonal | 10.9 cm (4.3") |
| Maximum duty cycle * | 350000 pages per month | Touchscreen | ✓ |
| Recommended duty cycle | 5000 - 100000 pages per month | Control type | Touch |
| Page description languages * | Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PPDS, PostScript 3 | Certification | RAL-UZ 205, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA, UL 60950-1, FCC Class A, cUL CAN / CSA-C22.2 60950-1, NOM, CB EN / IEC 60950-1, CB EN / IEC 60825-1, CE DoC (EN 62301 Class A, EN 62311, CE EN / IEC 60950-1, CE EN / IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER |
| Input & output capacity | | Power | |
| Total number of input trays * | 2 | Power consumption (ready) | 38.5 W |
| Total input capacity * | 650 sheets | Power consumption (standby) | 1.4 W |
| Total output capacity * | 550 sheets | Power consumption (off) | 0.2 W |
| Paper input type | Paper tray | Energy Star Typical Electricity Consumption (TEC) | 0.95 kWh/week |
| Maximum number of input trays | 6 | System requirements | |
| Maximum input capacity | 4400 sheets | Windows operating systems supported | ✓ |
| Maximum output capacity | 2550 sheets | Mac operating systems supported | ✓ |
| Paper handling | | Linux operating systems supported | ✓ |
| Maximum ISO A-series paper size * | A4 | Server operating systems supported | SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, SUSE Linux Enterprise Server 12, Windows 2000 Server, Windows Server 2012 |
| Paper tray media types * | Card stock, Envelopes, Labels, Plain paper, Transparencies | Operational conditions | |
| Multi-purpose tray media types | Envelopes, Executive, Labels, Legal, Letter, Plain paper, Transparencies | Operating temperature (T-T) | 10 - 32 °C |
| ISO A-series sizes (A0...A9) * | A4, A5, A6 | Operating relative humidity (H-H) | 8 - 80% |
| Non-ISO print media sizes | Executive, Folio, Legal, Letter, Oficio, Statement, Universal | Operating altitude | 0 - 2896 m |
| JIS B-series sizes (B0...B9) | B5 | Sustainability | |
| Envelopes sizes | 7 3/4, 9, 10, B5, C5, DL | Sustainability certificates | Blue Angel, ENERGY STAR |
| Paper tray media weight | 60 - 176 g/m ² | Weight & dimensions | |
| Ports & interfaces | | Width | 428 mm |
| Direct printing * | ✓ | | |
| USB port * | ✓ | | |
| USB connector | USB Type-A / USB Type-B | | |
| Optional connectivity | Parallel, Wireless LAN | | |
| Network | | | |
| Ethernet LAN * | ✓ | | |
| Cabling technology | 10/100/1000Base-T(X) | | |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | | |
| Security algorithms | HTTPS, IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMP, SNMPv3, SSL/TLS | | |

| Performance | | Weight & dimensions | |
|-------------------------|----------|---------------------|---------|
| Internal memory * | 1024 MB | Depth | 510 mm |
| Maximum internal memory | 5120 MB | Height | 441 mm |
| Built-in processor | ✓ | Weight | 25.6 kg |
| Processor frequency | 1000 MHz | Packaging data | |
| Processor cores | 2 | Package width | 550 mm |
| | | Package depth | 650 mm |
| | | Package height | 565 mm |
| | | Package weight | 30.6 kg |



0734646672474



734646672474

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.