

Epson M-L90Peeler (393) 203 x 203 DPI Wired Thermal POS printer

Brand : Epson

Product code: C31C412393

Product name : M-L90Peeler (393)

Thermal line, 150mm/sec, 203 x 203DPI, Ethernet, USB 2.0 Type A, 53dB, 140 x 148 x 203mm, 1.9kg

[Epson M-L90Peeler \(393\) 203 x 203 DPI Wired Thermal POS printer:](#)

Compact thermal label printer with convenient peeling function

Epson M-L90Peeler (393). Print technology: Thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 9 cm, Maximum printing width: 8 cm. Connectivity technology: Wired, Standard interfaces: Ethernet, USB 2.0. Sound pressure level (printing): 53 dB, Mean time between failures (MTBF): 360000 h, Country of origin: China. Product colour: Grey



| | | | |
|-----------------------------------|-------------------|---------------------------------|------------|
| Printing | | Operational conditions | |
| Maximum resolution | 203 x 203 DPI | Storage relative humidity (H-H) | 10 - 90% |
| Print speed | 150 mm/sec | Weight & dimensions | |
| Print technology * | Thermal | Width | 140 mm |
| Type * | POS printer | Depth | 148 mm |
| Paper handling | | Height | 203 mm |
| Maximum roll diameter | 9 cm | Weight | 1.9 kg |
| Maximum printing width | 8 cm | Packaging data | |
| Ports & interfaces | | Quantity per pack | 1 pc(s) |
| USB port * | ✓ | Package width | 193 mm |
| Connectivity technology * | Wired | Package depth | 250 mm |
| Standard interfaces | Ethernet, USB 2.0 | Package height | 240 mm |
| Network | | Package weight | 2.69 kg |
| Ethernet LAN * | ✓ | Logistics data | |
| Wi-Fi * | ✗ | Harmonized System (HS) code | 84433210 |
| Features | | Products per pallet | 112 pc(s) |
| Sound pressure level (printing) | 53 dB | Products per pallet layer | 16 pc(s) |
| Mean time between failures (MTBF) | 360000 h | Pallet gross width | 80 cm |
| Cutter | ✓ | Pallet gross length | 120 cm |
| Country of origin | China | Pallet gross height | 15 cm |
| Safety | TÜV | Products per pallet (UK) | 168 pc(s) |
| Design | | Products per pallet layer (UK) | 24 pc(s) |
| Product colour * | Grey | Pallet width (UK) | 100 cm |
| Operational conditions | | Pallet length (UK) | 120 cm |
| Operating temperature (T-T) | 5 - 45 °C | Pallet height (UK) | 15 cm |
| Storage temperature (T-T) | -10 - 50 °C | Other features | |
| | | Electromagnetic compatibility | CE marking |

Operational conditions

Operating relative humidity (H-H) 10 - 90%

Other featuresMean cycles between failures
(MCBF) 7000000



8715946617312

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-OCT-2024. Prints or copies of Information are only valid on the printed Publication date