



TP-Link TL-SG1005P Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : TP-Link

Tuotekoodi: TL-SG1005P V1

Tuotteen nimi : TL-SG1005P



TP-Link TL-SG1005P. Kytin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. MAC-osoitetaulukko: 2000 entries, Kytkentäkapasiteetti: 10 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x. DC-syöttöjännite: 48 V. Power over Ethernet -tuki



Management features		Power	
Switch type *	Unmanaged	Power source *	DC/PoE
Quality of Service (QoS) support	✓	Power supply included *	✓
Ports & interfaces		DC input voltage	48 V
Basic switching RJ-45 Ethernet ports quantity *	5	Input current	1.25 A
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power consumption (max)	64.44 W
Gigabit Ethernet (copper) ports quantity	5	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✓
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) ports quantity	4
10G support *	✗	Total Power over Ethernet (PoE) budget	56 W
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Operational conditions	
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6	Operating temperature (T-T)	0 - 40 °C
Flow control support	✓	Storage temperature (T-T)	-40 - 70 °C
Auto MDI/MDI-X	✓	Operating relative humidity (H-H)	10 - 90%
Auto-negotiation	✓	Storage relative humidity (H-H)	5 - 90%
MAC address auto-learning supported	✓	Heat dissipation	219.87 BTU/h
MAC address auto-aging supported	✓	Weight & dimensions	
Data transmission		Width	99.8 mm
Switching capacity *	10 Gbit/s	Depth	98 mm
Forwarding rate	7.44 Mpps	Height	25 mm
MAC address table *	2000 entries	Packaging content	
Store-and-forward	✓	User guide	✓
		Packaging data	
		AC adapter included	✓
		Package type	Box

Security		Packaging data	
IGMP snooping	✓	Package width	131 mm
Design		Package depth	196 mm
Rack mounting *	✗	Package height	121 mm
Stackable *	✗	Package weight	800 g
Product colour	Black	Sustainability	
LED indicators	✓	Sustainability compliance	✓
Performance		Certificates	
Maximum cable length	100 m	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Fanless	✓	Logistics data	
		Harmonized System (HS) code	85176990



6935364083212



6935364083229



0845973083212



845973083212

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.