## **ATEN**

## ATEN KA8288-AX-G KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: KA8288-AX-G

Tuotteen nimi: KA8288-AX-G







Ports & interfaces		Sustainability	
Keyboard port type *	USB	Compliance certificates	RoHS
Mouse port type * Video port type * HDMI ports quantity USB connector type Serial port type	USB HDMI 2 USB Type-A DE-9 (DB-9)	Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 60 °C 0 - 80%
Serial ports quantity	1	Weight & dimensions	
udio connections  leadphone outputs  lumber of microphone inputs  1  1  1  1  1  1  1  1  1  1  1  1  1	Width Depth Height Weight	155.4 mm 174.2 mm 28.8 mm 1.29 kg	
Network		Packaging data	
Ethernet LAN Ethernet LAN (RJ-45) ports Performance	<b>v</b> 1	Package width Package depth Package height Package weight	98 mm 325 mm 210 mm 1.49 kg
HD type *	Full HD+	Packaging content	
Maximum resolution * Video bandwidth	1920 x 1200 pixels 60 Hz	Cables included Manual	AC ✓
Design		AC adapter included	<b>√</b>
Rack mounting *	<b>✓</b>	Logistics data	
Product colour * Housing material LED indicators Push button	Black Metal Power ✔	Harmonized System (HS) code 8517 Master (outer) case width 342 i	6.45 kg 85176200 342 mm 512 mm
Display		Master (outer) case height	232 mm
Built-in display *	×	Master (outer) case gross weight	8.19 kg
Power		Products per master (outer) case	5 pc(s)
Power source Input voltage Power consumption (typical)	DC 5.3 V 6.53 W		

