



ATEN CL1016M telinekonsoli 43,2 cm (17") 1280 x 1024 pikseliä Metalli, Muovi musta 1U

Tuotemerkki : ATEN

Tuotekoodi: CL1016M-ATA-XG

Tuotteen nimi : CL1016M



ATEN CL1016M. Näytön halkaisija: 43,2 cm (17"), Näytön erottelutarkkuus: 1280 x 1024 pikseliä, Näyttö: TFT-LCD. Näppäimistöportin liitin: PS/2, Hiiriportin liitin: PS/2, Videoportin tyyppi: VGA. Virrankulutus: 24,5 W, AC-adapterin syöttöjännite: 100 - 240 V, AC-adapterin taajuus: 50 - 60 Hz. Tuotteen leveys: 640,2 mm, Tuotteen korkeus: 44 mm, Tuotteen syvyys: 480 mm. Pakkauksen paino: 16,8 kg, Pakkauksen leveys: 668 mm, Pakkauksen syvyys: 718 mm



Display		Power	
Display diagonal	43.2 cm (17")	AC adapter input voltage	100 - 240 V
Display resolution	1280 x 1024 pixels	AC adapter frequency	50 - 60 Hz
Display	TFT-LCD	Input current	1 A
Display brightness	250 cd/m ²	Operational conditions	
Contrast ratio (typical)	1000:1	Operating temperature (T-T)	0 - 50 °C
Viewing angle, horizontal	170°	Storage temperature (T-T)	-20 - 60 °C
Viewing angle, vertical	160°	System requirements	
On Screen Display (OSD)	✓	Windows operating systems supported	✓
Pixel pitch	0.264 x 0.264 mm	Linux operating systems supported	✓
Response time	5 ms	Weight & dimensions	
Display number of colours	16.78 million colours	Width	640.2 mm
Technical details		Height	44 mm
Material	Metal, Plastic	Depth	480 mm
Product colour	Black	Weight	13.6 kg
Operating relative humidity (H-H)	0 - 80%	Packaging data	
Maximum resolution	1920 x 1200 pixels	Package weight	16.8 kg
Rack mounting	✓	Package width	668 mm
Connector type	SPHD	Package depth	718 mm
Daisy chain	✓	Package height	135 mm
Number of computers controlled	16	Packaging content	
LED indicators	✓	Manual	✓
Rack capacity	1U	Logistics data	
Ports & interfaces		Master (outer) case net weight	13.6 kg
Keyboard port type	PS/2	Master (outer) case width	668 mm
Mouse port type	PS/2	Master (outer) case length	718 mm
Video port type	VGA	Master (outer) case height	135 mm
Keyboard		Master (outer) case gross weight	16.8 kg
Hot keys	✓	Products per master (outer) case	1 pc(s)
Power			
Power consumption (typical)	24.5 W		



4719264642432

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date