KYOCERA ECOSYS M2135dn Laser A4 1200 x 1200 DPI 35 ppm

Tuotemerkki: KYOCERA Tuoteperhe: ECOSYS Tuotekoodi: 1102S03NL0

Tuotteen nimi: M2135dn

KYOCERA ECOSYS M2135dn. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 1200 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600×600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600×600 DPI. Kaksipuolinen toiminto: Tulosta. Suurin ISO A-luokan paperikoko: A4. Suoratulostus. Tuotteen väri: musta, Valkoinen






Printing		Ports & interfaces	
Duplex printing mode Print technology * Printing * Duplex printing *	Auto Laser Mono printing	Standard interfaces Direct printing * USB port	Ethernet, USB 2.0 ✓
Maximum resolution * Print speed (black, normal quality,	1200 x 1200 DPI	USB 2.0 ports quantity Network	2
A4/US Letter) * Duplex print speed (black, normal quality, A4/US Letter)	35 ppm 17.5 ppm	Wi-Fi * Ethernet LAN *	×
Warm-up time Time to first page (black, normal) N-in-1 print function Tray protection function N-up printing Barcode printing	17 s 6.8 s • • 2, 4	Cabling technology Ethernet LAN data rates Bluetooth Near Field Communication (NFC) Mobile printing technologies	10/100/1000Base-T(X) 10,100,1000 Mbit/s X Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Watermark printing	· ✓	Performance	
Secure printing Booklet printing function Poster printing function Borderless printing	* * * * *	Maximum internal memory Card reader integrated Internal memory * Compatible memory cards	1536 MB ✓ 512 MB SD, SDHC
Copying		Built-in processor Processor family	✓ ARM Cortex-A9
Duplex copying * Copying *	X Mono copying	Processor frequency	800 MHz

Copying		Performance	
Maximum copy resolution *	600 x 600 DPI	Sound pressure level (printing)	51 dB
Copy speed (black, normal quality, A4)	35 cpm	Sound pressure level (copying)	51 dB
Time to first copy (black, normal)	6.9 s	Sound pressure level (quiet mode)	47 dB
Maximum number of copies	999 copies	Sound power level (standby)	29 dB
Copier resize	25 - 400%	Design	
N-in-1 copy function	✓	Product colour *	Black, White
N-in-1 copy function (N=)	2, 4	Market positioning *	Business
Copy programming function	·	Built-in display *	✓
ID-card copy function	✓	Display	LCD
Scanning		Display number of lines	5 lines
-		Power	
Duplex scanning *	X	Power consumption (average	661 W
Scanning *	Colour scanning	operating)	
Optical scanning resolution * Scan technology	600 x 600 DPI CIS	Power consumption (printing)	661 W 661 W
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	Power consumption (copying) Power consumption (ready)	21 W
Scan speed (colour)	23 ppm	Power consumption (sleep)	1 W
Scan speed (black)	40 ppm	Energy Star Typical Electricity	
Image formats supported	JPEG, TIF	Consumption (TEC)	1.47 kWh/week
Document formats supported	PDF, XPS	AC input voltage	220 - 240 V
Scan drivers	TWAIN, WIA	AC input frequency	50 - 60 Hz
Fax		System requirements	
Faxing *	x	Windows operating systems	✓
Features		supported	Mac OS X 10.10 Yosemite, Mac OS X
Recommended duty cycle	1000 - 2500 pages per month		10.11 El Capitan, Mac OS X 10.12
Maximum duty cycle *	20000 pages per month		Sierra, Mac OS X 10.13 High Sierra,
Duplex functions *	Print	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5
Digital sender	✓		Leopard, Mac OS X 10.6 Snow
Number of print cartridges *	1		Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X
Printing colours *	Black		10.9 Mavericks
Page description languages	Microsoft XPS, PCL 5e, PCL 6, PCL	Linux operating systems supported	✓
Page description languages	XL, PostScript 3	Linux operating systems supported Operational conditions	*
Number of printer fonts	XL, PostScript 3 93	. 5,	10 - 80%
Number of printer fonts Replacement cartridges	XL, PostScript 3	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T)	
Number of printer fonts Replacement cartridges Input & output capacity	XL, PostScript 3 93 TK-1150 (3.000 pagina's)	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T)	10 - 80%
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays *	XL, PostScript 3 93 TK-1150 (3.000 pagina's)	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H)	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90%
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity *	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity *	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H)	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90%
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF)	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets 100 sheets Cassette, Paper tray	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm 437 mm
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) Auto document feeder (ADF) Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size * Maximum print size	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets 150 sheets A4 216 x 356 mm	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size * Maximum print size Paper tray media types *	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets 150 sheets A4 216 x 356 mm Plain paper	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm 437 mm 19 kg
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size * Maximum print size Paper tray media types * ISO A-series sizes (A0A9) *	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets 150 sheets 150 sheets 44 216 x 356 mm Plain paper A4, A5, A6	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm 437 mm 19 kg
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size * Maximum print size Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9)	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets 150 sheets A4 216 x 356 mm Plain paper A4, A5, A6 B5, B6	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm 437 mm 19 kg 541 mm 555 mm
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size * Maximum print size Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets 150 sheets 150 sheets 150 sheets Legal, Letter	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm 437 mm 19 kg 541 mm 555 mm 572 mm
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size * Maximum print size Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes Custom media width	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets 150 sheets 150 sheets 150 sheets 150 sheets 150 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm 437 mm 19 kg 541 mm 555 mm
Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size * Maximum print size Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes	XL, PostScript 3 93 TK-1150 (3.000 pagina's) 1 250 sheets 150 sheets 250 sheets ✓ 100 sheets Cassette, Paper tray ✓ 50 sheets 3 850 sheets 150 sheets 150 sheets 150 sheets Legal, Letter	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m GS, TÜV, CE, ISO 9001, ISO 14001 Blue Angel, EPEAT Silver, ENERGY STAR 417 mm 412 mm 437 mm 19 kg 541 mm 555 mm 572 mm

Paper handling		Packaging content	
Multi-Purpose Tray media weight Duplex media weight	60 - 220 g/m ² 60 - 163 g/m ²	Cartridge(s) included	1
		Included cartridge capacity (black)	1000 pages
		lmaging unit included	✓
		Cables included	AC
		Logistics data	
		Harmonized System (HS) code	84433100
		Technical details	
		Compliance certificates	REACH, RoHS
		Other features	
		Cartridge type	TK-1150









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.