## KYOCERA ECOSYS M3145dn Laser A4 1200 x 1200 DPI 45 ppm

Tuotemerkki: KYOCERA Tuoteperhe: ECOSYS Tuotekoodi: 1102TF3NL0

Tuotteen nimi: M3145dn

KYOCERA ECOSYS M3145dn. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 1200 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Kaksipuolinen toiminto: Kopiointi, Tulosta, Skannaus. Suurin ISO A-luokan paperikoko: A4. Suoratulostus. Tuotteen väri: musta, Valkoinen





Printing		Paper handling	
Duplex printing mode Print technology *	Auto Laser	Auto Document Feeder (ADF) media weight	50 - 120 g/m²
Printing *	Mono printing	Duplex media weight	60 - 120 g/m²
Duplex printing *	✓	Ports & interfaces	
Maximum resolution *	1200 x 1200 DPI	Standard interfaces	Ethernet, USB 2.0
Print speed (black, normal quality, A4/US Letter) *	45 ppm	Direct printing *	<b>/</b>
Duplex print speed (black, normal quality, A4/US Letter)	22.5 ppm	USB port USB 2.0 ports quantity	3
Warm-up time	16 s	Optional connectivity	Ethernet, Wireless LAN
Time to first page (black, normal)	5.9 s	Network	
N-in-1 print function	✓	Wi-Fi *	X
N-up printing	2, 4	Ethernet LAN *	· •
Watermark printing	✓	Cabling technology	10/100/1000Base-T(X)
Secure printing	<b>✓</b>	Ethernet LAN data rates	10,100,1000 Mbit/s
Poster printing function	✓	Bluetooth	X
Borderless printing	×	Near Field Communication (NFC)	×
Copying		Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print
Duplex copying *	✓	Mobile printing technologies	Service
Duplex copying mode	Auto Mana sanying	Performance	
Copying *  Maximum copy resolution *	Mono copying 600 x 600 DPI	Maximum internal memory	3000 MB
Maximum copy resolution *	000 X 000 DI I	Card reader integrated	✓

Copying		Performance	
Copy speed (black, normal quality, A4)	45 cpm	Internal memory * Compatible memory cards	1000 MB SD, SDHC
Time to first copy (black, normal)	7 s	Built-in processor	<b>✓</b>
Maximum number of copies	999 copies	Processor family	ARM Cortex-A9
Copier resize	25 - 400%	Processor frequency	1200 MHz
N-in-1 copy function	<b>✓</b>	Processor cores	2
N-in-1 copy function (N=)	2, 4	Coprocessor frequency	1.2 GHz
Copy programming function	✓	Sound pressure level (printing)	54 dB
ID-card copy function	✓	Sound pressure level (copying)	54 dB
Scanning		Sound power level (standby)	30 dB
Duplex scanning *	<b>✓</b>	Design	
Duplex scanning mode	Auto	Product colour *	Black, White
Scanning *	Colour scanning	Market positioning *	Business
Optical scanning resolution *	600 x 600 DPI	Built-in display *	✓
Scan technology	CIS	Display	LCD
Scan to	E-mail, FTP, SMB, TWAIN, WIA	Control type	Buttons
Scan speed (colour)	40 ppm	Colour display	×
Scan speed (black)	60 ppm	Power	
Duplex scan speed (colour)  Duplex scan speed (black)	17 ppm 26 ppm	Power consumption (average	630 W
Image formats supported	JPEG, TIFF	operating)	
Document formats supported	PDF, XPS	Power consumption (PowerSave)	29 W
Greyscale levels	256	Power consumption (printing)	630 W
Scan drivers	TWAIN, WIA	Power consumption (copying)	652 W 50 W
Fax		Power consumption (ready) Power consumption (sleep)	0.5 W
Faxing *	<b>~</b>	Energy Star Typical Electricity	
	X	Consumption (TEC)	2.25 kWh/week
Features		AC input voltage	220 - 240 V
Recommended duty cycle	3000 - 10000 pages per month	AC input frequency	50 - 60 Hz
Maximum duty cycle *  Duplex functions *	150000 pages per month	System requirements	
Digital sender	Copy, Print, Scan	Windows operating systems	<b>✓</b>
Number of print cartridges *	1	supported	Mac OS X 10.10 Yosemite, Mac OS X
Printing colours *	Black		10.11 El Capitan, Mac OS X 10.12
Page description languages	OpenXPS, PCL 6, TIFF, XPS	Mac operating systems supported	Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X
Printer fonts	Barcode, Bitmap, PCL, Windows	Mac operating systems supported	10.15 Catalina, Mac OS X 10.8
All-In-One-multitasking	<b>✓</b>		Mountain Lion, Mac OS X 10.9
Replacement cartridges	TK-3160 (12.500 pagina's)	Linux operating systems supported	Mavericks •
Input & output capacity		. 3,	•
Total number of input trays *	1	Operational conditions	15 00%
Total input capacity *	500 sheets	Operating relative humidity (H-H) Storage temperature (T-T)	15 - 80% -20 - 40 °C
Total output capacity *	250 sheets	Operating temperature (T-T)	-20 - 40 °C 10 - 32.5 °C
Paper tray 1 input capacity	500 sheets	Storage relative humidity (H-H)	10 - 90%
Multi-Purpose tray	<b>V</b>	Operating altitude	0 - 3500 m
Multi-Purpose tray input capacity	100 sheets	Non-operating altitude	0.6 - 15000 m
Paper input type	Cassette, Paper tray	Certificates	
Auto document feeder (ADF)	✓	Waste Electrical and Electronic	
Auto document feeder (ADF) input capacity	75 sheets	Equipment (WEEE) compliance	✓
Maximum number of input trays	5	Certification	TÜV/GS, CE, ISO 9001, ISO 14001.
Maximum input capacity	2600 sheets	Sustainability	
Maximum output capacity	250 sheets	Sustainability certificates	Blue Angel, EPEAT Silver, ENERGY
		Sustainability Certificates	STAR
Paper handling			
Paper handling  Maximum ISO A-series paper size *	A4	Weight & dimensions	
Maximum ISO A-series paper size * Maximum print size	A4 216 x 356 mm	Weight & dimensions Width	475 mm
Maximum ISO A-series paper size *	216 x 356 mm Plain paper	Width Depth	476 mm
Maximum ISO A-series paper size * Maximum print size Paper tray media types *	216 x 356 mm Plain paper Envelopes, Labels, Legal, Letter,	Width Depth Height	476 mm 575 mm
Maximum ISO A-series paper size * Maximum print size	216 x 356 mm Plain paper	Width Depth	476 mm

Paper handling		Packaging data	
ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes Custom media width Custom media length Paper tray media weight Multi-Purpose Tray media weight	A4, A5 B5, B6 Folio, Legal, Letter 140 - 216 mm 148 - 356 mm 60 - 120 g/m <sup>2</sup> 60 - 220 g/m <sup>2</sup>	Package width Package depth Package height Package weight  Packaging content  Cartridge(s) included Included cartridge capacity (black) Imaging unit included	589 mm 572 mm 695 mm 29.3 kg
		Cables included	AC
		Logistics data	
		Harmonized System (HS) code	84433100
		Technical details	
		Compliance certificates	REACH, RoHS





632983051023

0632983051023

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.