

# KYOCERA ECOSYS M3645idn Laser A4 1200 x 1200 DPI 45 ppm

**Tuotemerkki :** KYOCERA

**Tuoteperhe:** ECOSYS

**Tuotekoodi:** 1102V33NLO

**Tuotteen nimi :** M3645idn



KYOCERA ECOSYS M3645idn. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 1200 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Faksaus: Yksittäisfaksin lähetyks. Kaksipuolinen toiminto: Kopiointi, Faksi, Tulosta, Skannaus. Suurin ISO A-luokan paperikoko: A4. Suoratulostus. Tuotteen väri: musta, Valkoinen

Printing		Paper handling	
Duplex printing mode	Auto	Multi-Purpose Tray media weight	60 - 220 g/m <sup>2</sup>
Print technology *	Laser	Auto Document Feeder (ADF) media weight	50 - 120 g/m <sup>2</sup>
Printing *	Mono printing	Duplex media weight	60 - 120 g/m <sup>2</sup>
Duplex printing *	✓	Ports & interfaces	
Maximum resolution *	1200 x 1200 DPI	Standard interfaces	Ethernet, USB 2.0
Print speed (black, normal quality, A4/US Letter) *	45 ppm	Direct printing *	✓
Duplex print speed (black, normal quality, A4/US Letter)	22.5 ppm	USB port	✓
Warm-up time	21 s	USB 2.0 ports quantity	3
Time to first page (black, normal)	5.9 s	Optional connectivity	Ethernet, Wireless LAN
N-in-1 print function	✓	Network	
N-up printing	2, 4	Wi-Fi *	✗
Watermark printing	✓	Ethernet LAN *	✓
Economical printing	✓	Cabling technology	10/100/1000Base-T(X)
Secure printing	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Poster printing function	✓	Bluetooth	✗
Borderless printing	✗	Near Field Communication (NFC)	✗
Copying		Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Duplex copying *	✓	Performance	
Duplex copying mode	Auto	Maximum internal memory	3000 MB
Copying *	Mono copying	Internal memory *	1000 MB
Maximum copy resolution *	600 x 600 DPI	Compatible memory cards	SD, SDHC
Copy speed (black, normal quality, A4)	45 cpm	Built-in processor	✓
Time to first copy (black, normal)	7 s	Processor family	ARM Cortex-A9
Maximum number of copies	999 copies	Processor frequency	1200 MHz
Copier resize	25 - 400%	Processor cores	2
N-in-1 copy function	✓	Coprocessor frequency	1.2 GHz
N-in-1 copy function (N=)	2, 4	Sound pressure level (printing)	54 dB
Copy programming function	✓	Sound pressure level (copying)	54 dB
ID-card copy function	✓	Sound power level (standby)	30 dB
Scanning		Design	
Duplex scanning *	✓	Product colour *	Black, White
Duplex scanning mode	Auto	Market positioning *	Business

<b>Scanning</b>		<b>Design</b>	
Scanning *	Colour scanning	Built-in display *	✓
Optical scanning resolution *	600 x 600 DPI	Display	TFT
Maximum scan area	216 x 356 mm	Display diagonal	17.8 cm (7")
Scan technology	CIS	Touchscreen	✓
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	Control type	Touch
Scan speed (colour)	40 ppm	Colour display	✓
Scan speed (black)	60 ppm	<b>Power</b>	
Duplex scan speed (colour)	17 ppm	Power consumption (average operating)	630 W
Duplex scan speed (black)	26 ppm	Power consumption (printing)	630 W
Image formats supported	JPEG, TIFF	Power consumption (copying)	652 W
Document formats supported	PDF, XPS	Power consumption (ready)	50 W
Greyscale levels	256	Power consumption (sleep)	0.5 W
Scan drivers	TWAIN, WIA	Energy Star Typical Electricity Consumption (TEC)	2.38 kWh/week
<b>Fax</b>		AC input voltage	220 - 240 V
Duplex faxing	✓	AC input frequency	50 - 60 Hz
Faxing *	Mono faxing	<b>System requirements</b>	
Fax resolution (black)	400 x 400 DPI	Windows operating systems supported	✓
Fax transmission speed	3 sec/page		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Modem speed	33.6 Kbit/s	Mac operating systems supported	
Fax memory	256 pages	Linux operating systems supported	✓
Speed dialling	✓	<b>Operational conditions</b>	
Fax coding methods	JBIG, MH, MMR, MR	Operating relative humidity (H-H)	15 - 80%
<b>Features</b>		Storage temperature (T-T)	-20 - 40 °C
Recommended duty cycle	3000 - 10000 pages per month	Operating temperature (T-T)	10 - 32.5 °C
Maximum duty cycle *	25000 pages per month	Storage relative humidity (H-H)	10 - 90%
Duplex functions *	Copy, Fax, Print, Scan	Operating altitude	0 - 3500 m
Digital sender	✓	Non-operating altitude	0.6 - 15000 m
Number of print cartridges *	1	<b>Certificates</b>	
Printing colours *	Black	Waste Electrical and Electronic Equipment (WEEE) compliance	✓
Page description languages	OpenXPS, PCL 6, TIFF, XPS	Certification	TÜV/GS, CE, ISO 9001, ISO 14001.
Replacement cartridges	TK-3060 (14.500 pagina's)	<b>Sustainability</b>	
<b>Input &amp; output capacity</b>		Sustainability certificates	Blue Angel, EPEAT Silver, ENERGY STAR
Total number of input trays *	1	<b>Weight &amp; dimensions</b>	
Total input capacity *	500 sheets	Width	475 mm
Total output capacity *	250 sheets	Depth	476 mm
Paper tray 1 input capacity	500 sheets	Height	575 mm
Multi-Purpose tray	✓	Weight	23 kg
Multi-Purpose tray input capacity	100 sheets	<b>Packaging data</b>	
Paper input type	Cassette, Paper tray	Package width	589 mm
Auto document feeder (ADF)	✓	Package depth	572 mm
Auto document feeder (ADF) input capacity	75 sheets	Package height	695 mm
Maximum number of input trays	5	Package weight	29.8 kg
Maximum input capacity	2600 sheets	<b>Packaging content</b>	
Maximum output capacity	250 sheets	Cartridge(s) included	✓
<b>Paper handling</b>		Included cartridge capacity (black)	6000 pages
Maximum ISO A-series paper size *	A4	Imaging unit included	✓
Paper tray media types *	Plain paper	Cables included	AC
	Envelopes, Labels, Legal, Letter, Plain paper, Recycled paper, Thick paper, Thin paper		
Multi-purpose tray media types			
ISO A-series sizes (A0...A9) *	A4, A5		
ISO B-series sizes (B0...B9)	B5, B6		
Non-ISO print media sizes	Folio, Legal, Letter		
Custom media width	70 - 216 mm		
Custom media length	148 - 356 mm		
Paper tray media weight	60 - 120 g/m <sup>2</sup>		

**Logistics data**

Harmonized System (HS) code 84433100

**Technical details**

Compliance certificates REACH, RoHS



0632983051092



632983051092

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.