

## D-Link DGS-1005P/E verkkokytin Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

**Tuotemerkki :** D-Link

**Tuotekoodi:** DGS-1005P/E

**Tuotteen nimi :** DGS-1005P/E

D-Link DGS-1005P/E. Kytin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. Täysin kaksipuolinen. MAC-osoitetaulukko: 2000 entries, Kytkentäkapasiteetti: 10 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE.... Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki. Seinäkiinnitteinen



Management features		Design	
Switch type *	Unmanaged	Housing material	Metal
Quality of Service (QoS) support	✓	LED indicators	Activity, Link, PoE, Power, Speed, Status
Ports & interfaces		Wall mountable	✓
Basic switching RJ-45 Ethernet ports quantity *	5	Performance	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Buffer size	64 KB
Gigabit Ethernet (copper) ports quantity	5	Plug and Play	✓
Power connector	DC-in jack	Power	
Network		Power supply included *	✓
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) ports quantity	4
Full duplex	✓	Power over Ethernet (PoE) power per port	30 W
Auto MDI/MDI-X	✓	Total Power over Ethernet (PoE) budget	60 W
Auto-negotiation	✓	Operational conditions	
MAC address auto-learning supported	✓	Operating temperature (T-T)	0 - 40 °C
Data transmission		Storage temperature (T-T)	-10 - 70 °C
Switching capacity *	10 Gbit/s	Operating relative humidity (H-H)	0 - 95%
Forwarding rate	7.44 Mpps	Storage relative humidity (H-H)	0 - 95%
MAC address table *	2000 entries	Weight & dimensions	
Store-and-forward	✓	Width	100 mm
Security		Depth	98 mm
Packet filtering	7.44 Mpps	Height	28 mm
Design		Weight	260 g
Rack mounting *	✗	Certificates	
Product colour	Black	Certification	CE, BSMI, FCC , VCCI, RCM, cUL, CB, LVD, BSMI



0790069440984



790069440984

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.