## **Epson WorkForce DS-80W**

Brand : Epson

Product family: WorkForce

Product code: B11B253402

Product name : WorkForce DS-80W

- Scan anywhere: Small, lightweight design

- USB cable or integrated battery power: Scan up to 300 pages between battery charges

- Fast scanning speeds: At up to four seconds per page (8.5ppm)

- Simplify your workload: Continuous scanning with automatic feed mode

- Includes a range of software: Document Capture Pro 2, Epson Scan 2.0 and TWAIN driver support WorkForce DS-80W

Epson WorkForce DS-80W. Maximum scan size: 216 x 1828 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 48 bit. Scanner type: Handheld scanner, Product colour: White, Display: LCD. Sensor type: CIS, Daily duty cycle (max): 300 pages, Light source: ReadyScan LED. Auto document feeder (ADF) input capacity: 1 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), Paper tray media weight: 35 - 270 g/m<sup>2</sup>





Scanning		Packaging data	
Maximum scan size *	216 x 1828 mm	Package depth	330 mm
Optical scanning resolution *	600 x 600 DPI	Package height	67 mm
Colour scanning	1	Package weight	597 g
Duplex scanning *	×	Packaging content	
Input colour depth	48 bit	Cables included	USB
Output colour depth Input greyscale depth	24 bit 16 bit 8 bit	Bundled software	Document Capture Pro 2.0, Epson Scan 2
Output greyscale depth		System requirements	
Output monochrome depth Scan speed (b/w, low res, A4) Scan speed (colour, low res, A4)	8 bit 4 sec/page 4 sec/page	Compatible operating systems	Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003, Windows Server 2008 (32/64 Bit), Windows
Design Scanner type *	Handheld scanner		Server 2012 R2, Windows Server 2016, Windows Vista, Windows XP
Product colour * Display	White LCD	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP
Colour display	X		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Built-in display *	✓	Mac operating systems supported Mac OS X 10.13 High Sierr Mac OS X 10.14 Mojave, Mac OS 10.6 Snow Leopard, Mac OS X 10 Lion, Mac OS X 10.8 Mountain Lio Mac OS X 10.9 Mavericks	
Performance			
Sensor type * Light source	CIS ReadyScan LED		
Scan file formats Daily duty cycle (max) * Scan drivers	BMP, JPEG, PDF, PNG, TIFF 300 pages TWAIN, WIA, SANE, ICA	Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2008 x64, Windows Server 2012 R2, Windows Server 2016
Input capacity		Operational conditions	
Auto document feeder (ADF) input	1 sheets	Operating temperature (T-T)	5 - 35 °C
capacity		Storage temperature (T-T)	-25 - 60 °C
Paper handling		Operating relative humidity (H-H)	10 - 85%
Scanning media types supported	Business Card, Plastic Card, Post	Storage relative humidity (H-H)	10 - 90%
Maximum ISO A-series paper size *	Card(JPN) A4	Other features	
Paper tray media weight	35 - 270 g/m²	Output resolutions Image formats supported	600 dpi BMP, JPEG, TIFF, PNG

Paper handling		Logistics data	
Auto Document Feeder (ADF) media 35 - 270 g/m² weight		Products per pallet Country of origin	360 pc(s) China
Ports & interfaces USB port * USB version Standard interfaces Network Wi-Fi Power	✓ 2.0 USB 2.0, Wireless LAN	Pallet gross weight       0         Master (outer) case length       30         Master (outer) case height       32         Master (outer) case width       32         Master (outer) case gross weight       0         Pallet gross length       12         Pallet gross height       12         Pallet gross height       12         Products per master (outer) case       14         Products per pallet layer       64	0 g 360 mm 320 mm 350 mm 0 g 120 cm 80 cm 171 cm 10 pc(s) 60 pc(s) 60 pc(s)
Power supply type * Weight & dimensions	USB		
Width Depth Height Weight Packaging data	272 mm 47 mm 34 mm 300 g	Products per pallet (UK) Pallet weight (UK) Pallet length (UK) Pallet width (UK) Pallet height (UK) Master (outer) case GTIN (EAN/UPC)	360 pc(s) 0 g 120 cm 100 cm 171 cm
Quantity per pack Package width	1 pc(s) 141 mm	Harmonized System (HS) code 84716070	



8715946662848

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.