## **ATEN**

## ATEN CM1284 KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: CM1284-AT-G

Tuotteen nimi: CM1284

ATEN CM1284. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: HDMI. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Videokaistanleveys: 30 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Voimanlähde: AC, Tulojännite: 110 - 220 V, AC-syöttötaajuus: 50 - 60 Hz. Vaatimustenmukaisuustodistukset: RoHS





| Ports & interfaces                                   |                               | Display   |                     |
|--|-------------------------------|---|---------------------|
| Number of computers controlled *                     | 4                             | On Screen Display (OSD)                                       | ✓                   |
| Keyboard port type *                                 | USB                           | Power   |                     |
| Mouse port type *                                    | USB                           | Power source  | AC                  |
| Video port type *                                    | HDMI                          | Input voltage   | 110 - 220 V         |
| HDMI ports quantity                                  | 6<br>4                        | AC input frequency  | 50 - 60 Hz          |
| USB 2.0 Type-B ports quantity  Console ports *       | 3.5mm headphone, HDMI, RJ-45, | Input current   | 1 A                 |
| •  | USB A                         | Power consumption (typical)                                   | 16 W                |
| Console USB ports quantity                           | 2                             | Sustainability  |                     |
| USB hub  | <b>✓</b>                      | Compliance certificates                                       | RoHS                |
| USB 2.0 Type-A hub ports quantity USB connector type | 2<br>USB Type-A, USB Type-B   | Operational conditions  |                     |
| Audio connections                                    | <b>⊘</b>                      | Operating temperature (T-T)                                   | 0 - 40 °C           |
| Headphone outputs                                    | 6                             | Storage temperature (T-T)                                     | -10 - 60 °C         |
| Number of microphone inputs                          | 6                             | Operating relative humidity (H-H)                             | 0 - 80%             |
| Network  | ·                             | Weight & dimensions   |                     |
| Ethernet LAN   | 1                             | Width   | 437.2 mm            |
|  | 2                             | Depth   | 164 mm              |
| Ethernet LAN (RJ-45) ports                           | 2                             | Height  | 44 mm               |
| Performance  |                               | Weight  | 3.86 kg             |
| HD type *  | 4K Ultra HD                   | Packaging data  |                     |
| Maximum resolution *                                 | 4096 x 2160 pixels            | Package width   | 131 mm              |
| Video bandwidth                                      | 30 Hz                         | Package depth   | 540 mm              |
| Scan interval  | 5,10,15,30,60,90 s            | Package height  | 233 mm              |
| HDCP   | <b>✓</b>                      | Package weight  | 4.26 kg             |
| Hot-Plug support                                     | <b>✓</b>                      | Packaging content   |                     |
| Daisy chain  | <b>✓</b>                      | Cables included   | HDMI, USB           |
| Firmware upgradeable                                 | <b>V</b>                      | Manual  | 1                   |
| Design   |                               | AC adapter included   | ✓                   |
| Rack mounting *                                      | ✓                             | Rack mount kit  | ✓                   |
| Rack capacity  | 1U<br>Block                   | Logistics data  |                     |
| Product colour * Housing material                    | Black<br>Metal                | Master (outer) case net weight<br>Harmonized System (HS) code | 11.6 kg<br>85176200 |

| Design             |          | Logistics data                           |  |
|--------------------|----------|--|--|
| Cascadable         | ✓        | Master (outer) case width 420 mm         |  |
| LED indicators     | ✓        | Master (outer) case length 555 mm        |  |
| Push button        | /        | Master (outer) case height 258 mm        |  |
| Hot keys           |          | Master (outer) case gross weight 13.8 kg |  |
| not keys           | <b>,</b> | Products per master (outer) case 3 pc(s) |  |
| Display            |          |  |  |
| Built-in display * | X        |  |  |



4719264647505

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.