

# CITIZEN

## Two-inch label printing in a portable and rugged design

For Apple, Android and Windows Mobile



## CITIZEN CMP-25L

**MOBILE**

### Applications

- Price markdown
- Courier parcel pickup
- Bedside medical labelling
- Warehouse pick and pack



### Simple design, intuitive operation

The CMP-25L printer is designed like all Citizen printers to be simple to use and easy to operate.

This, combined with the durable, strong plastic case which is designed to take the occasional knock, means our printers keep running and running.



# CITIZEN

## LCD for status and configuration

The CMP-25L features an integral LCD display to allow the user to easily see the printer's status and, if needed, make quick changes to the printer's configuration.



## Specifications

Printer Model		Citizen CMP-25L
Printer Size and Type		2-inch Label and Receipt
Printing method		Line thermal dot printing
Printing speed		Up to 127 mm per second, 5 ips
Printing width		48 mm, 1.88 inches
Media width		13 - 58 mm, 0.5 to 2.28 inches - user adjustable
Media roll size		Diameter up to 56 mm
Characters and Fonts		Font A to H, Font GS, Resident TrueType (font 0) and downloadable TrueType
Media type		Thermal labels and receipts
Media sensors		Label Gap, Black Mark (Upper & Lower)
Resolution, Dots per line		203 dpi, 384 dots per line
Interface versions	RS232C Serial	Standard. Up to 115,000 baud, 7 or 8 bit (mini-DIN connector)
	USB	Standard. USB 2.0 full speed (mini connector, type B)
	Bluetooth	Factory Option: Version 4.2 + LE (Low Energy), Class 2, SPP profile, Apple® MFi® compliant
	Wireless LAN	Factory Option: 802.11a/b/g/n, 2.4 and 5.0 Ghz, including WEP, WPA, WPA2 (PSK & Enterprise)
Case design		Heavy duty plastic with impact resistance edge mouldings
Control Panel		Mono graphic LCD for easy setup and clear status
Environmental rating, drop test		Exceeds IP42. Survives multiple drops of 1.5 metres.
Physical dimensions (W x D x H)		100 x 158 x 85 mm
Printer weight (incl. battery, excl. paper)		580 grams (1.28 lbs)
Battery type and capacity		Li-Ion, 7.4 volt, 2600 mAh
Charger specification		Input: 100V-240V AC, 50/60Hz. Output: 8.4 volts, 1200 mA
Emulations		ZPL® emulation as standard
Drivers		Drivers, SDKs and/or Utilities for Windows, Apple iOS, Android and other operating systems

All product names are trademarks of the respective manufacturers. Windows is a trademark of Microsoft Corporation. Bluetooth® is a registered trademark of the Bluetooth SIG and WiFi is the registered trademark of the Wi-Fi Alliance. Android™ is a trademark of Google Inc., IOS™ is a trademark of Cisco Systems. CPCL and ZPL are registered trademarks of ZIH Corp. Apple® and Apple MFi® are trademarks of Apple Inc. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

# CITIZEN CMP-25L

**MOBILE**

## Features & Benefits

- Easy, drop-in paper loading and paper out indicators.
- Integral tear bar to cut labels at the gap
- Lithium Ion power technology and easy-change battery packs.
- Long life operation on one charge of the 2600 mAh battery
- Range of interfacing options including USB and Serial plus Bluetooth® and Wireless LAN networking options.
- Bluetooth 4.2 low energy compliant and Apple MFi approved
- Windows, iOS and Android drivers and software development toolkits for a range of application platforms.

