

APC Easy 3S uninterruptible power supply (UPS) Doubleconversion (Online) 10 kVA 10000 W

Brand : APC

Product code: E3SUPS10KH

Product name : Easy 3S


APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 10 kVA, Output power: 10000 W. Form factor: Tower, Product colour: White, International Protection (IP) code: IP20. Certification: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE. Width: 250 mm, Depth: 700 mm, Height: 530 mm. Package width: 400 mm, Package depth: 700 mm, Package height: 772 mm





| Features | | Design | |
|---|--|--|---|
| UPS topology * | Double-conversion (Online) | Product colour * | White |
| Output power capacity * | 10 kVA | International Protection (IP) code | IP20 |
| Output power * | | Operational conditions | |
| Vaveform *Pure sinenput operation voltage (min) *304 Vnput operation voltage (max) *477 Vnput frequency *45/65 HzOutput operation voltage (min)380 VOutput operation voltage (max)415 VOutput frequency50/60 Hz | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude | 0 - 40 °C -15 - 40 °C 0 - 95% 0 - 95% 0 - 984.3 m 0 - 14763.6 m | |
| Maximum current | 18 A | Certificates | |
| Number of input phases Number of output phases Input power factor | 3 3 0.99 | Certification | CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE |
| Crest factor | 3:1 | Packaging content | |
| Overload capacity (10 minutes) | 125% | Quick installation guide | 1 |
| Overload capacity (1 minute) | 150% | Weight & dimensions | |
| Output voltage Total Harmonic Distortion (THD) | 3% | Width | 250 mm |
| Input current Total Harmonic Distortion (THD) | 3% | Depth Height | 700 mm 530 mm |
| Noise level | 60 dB | Weight | 36 kg |
| Power protection features | Overload | Packaging data | |
| Design | | Package width | 400 mm |
| Form factor * | Tower | Package depth Package height | 700 mm 772 mm |

| Packaging data | | | | |
|-----------------------------|----------|--|--|--|
| Package weight | 50 kg | | | |
| Logistics data | | | | |
| Harmonized System (HS) code | 85078000 | | | |
| Other features | | | | |
| Output voltage | 400 V | | | |





731304339328

0731304339328

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.